

# CS 62 18.0-EC C

Cordless circular saw with pendulum hood 18 V

Order no. 491322

GTIN 4030293221260



- + Ideal for traditional applications in dry construction and refurbishing, e.g. for making saw cuts through plasterboard, concrete fibre boards, wood materials, such as formwork panels and chipboard or OSB boards
- + Brushless motor with greater efficiency and a longer service life
- + 18 V EC motor with overload protection and temperature monitoring
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Angle scale from 0 ° to 50 °. With preset angles of 22.5°/ 45°, and 50°. Easy to read, precision adjustment via non-slip clamping elements
- + Dual clamped swivel element prevents the saw blade from jamming when making mitre cuts and therefore the risk of recoil
- + Swivel range from 0° to 50° for undercuts as well as scoring function for perfect visible edges
- + Intuitive clamp lever for cutting depth adjustment, cutting depth is easy to read off
- + In accordance with the latest regulations without splitting wedge for plunge cuts and without time-consuming removal of splitting wedge
- + Spindle lock: for quick replacement of blades
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger
- + Woodshaving collection bag for low-dust operation, simple to empty, tool-free attachment by means of bayonet connection



## Technical data

|                                |                     |
|--------------------------------|---------------------|
| Battery voltage                | 18 V                |
| Battery capacity               | 2.5 / 5.0 / 8.0 Ah  |
| Max. no-load speed             |                     |
| Cutting depth                  | 0-62 mm             |
| Cutting depth, mitre cut (45°) | 0-38 mm             |
| Saw blade diameter             | 165 mm              |
| Saw blade hole                 | 20 mm               |
| Pivoting range                 | 0-50°               |
| Angle preset                   | 0 / 22,5 / 45 / 50° |
| Dimensions WxLxH               | 380 x 150 x 200 mm  |
| Weight without battery pack    | 3.1 kg              |

## Standard equipment

- 1 Standard circular saw blade with alternating teeth (456012)
- 1 Dust bag

