

CSM 4060

Metal-cutting circular saw for dry cutting

Order no. 307815

GTIN 4030293113084



- + For accurate metal cutting without coolant
- + Chip collection compartment with sight glass: large capacity, tool-free emptying
- + Special carbide-tipped saw blades: nearly burr-free cuts, trimming threaded bars possible without recutting the thread
- + Solid material / flat steel: 6 mm; -Round material: 20 mm; - Hollow sections: 63 mm
- + Tool-free adjustable guide plate, continuous saw depth adjustment to 63 mm
- + Switch: with lock-off / lock-on switch
- + Spindle lock



Technical data

Power consumption	1400 W
Power output	720 W
Voltage	230 V
Frequency	50/60 Hz
Max. no-load speed	
Cutting depth	0-63 mm
Saw blade diameter	185 mm
Saw blade hole	20 mm
Max. material thickness in aluminium 250 N/mm ²	6 mm
Max. material thickness in steel 400 N/ mm ²	10 mm
Cable length	4,0 m
Dimensions WxLxH	370 x 260 x 200 mm
Weight	5,4 kg

Standard equipment

- 2 Carbide tipped saw blade for steel (312304)
- 1 Parallel stop (312312)
- 1 Combination wrench (312347)
- 1 Safety glasses
- 1 Carrying case

www.flex-tools.com

this is performance **FLEX**