

VAC 800-EC

Building site air purifier, dust class M

Order no. 477745

GTIN 4030293213302



- + For cleaning air during renovation and demolition work in very hazardous black areas. To protect users, fine respirable dust is filtered from the air by means of coarse, fine, M/H filters and activated carbon filters
- + Dust is removed directly from wherever it is produced. A low pressure regime can be achieved by installing mobile plastic partitioning and air locks, thus preventing dust from spreading outside the work area.
- + Volume flow monitoring and variable volume flow setting via rotary switch. The low pressure required can thus be freely adjusted and adapted to the working environment
- + Brushless motor with greater efficiency and a longer service life
- + Low operating noise, with night function
- + Compact design, lightest tool of its class with 125 Ø mm exhaust air flow system
- + High air flow



Technical data

| | |
|--|-----------------------|
| Power consumption | 170 W |
| Nominal power consumption | 1,7-1,45 A |
| Voltage | 230 V |
| Frequency | 50/60 Hz |
| Fuse protection C | 10 A |
| Max. flow rate, air purifier | 544 m ³ /h |
| Filter surface, air cleaner | 7,26 m ² |
| Air purifier dust extraction connection diameter | 125 mm |
| Cable length | 3,5 m |
| Dimensions WxLxH | 373 x 400 x 508 mm |
| Weight | 7,2 kg |
| Sound pressure level in acc. with EN 60745 | 58 dB(A) |

Standard equipment

- 10 Pre-filter mats G3 (477699)
- 1 Coarse filter G4 (477702)
- 1 Filter HEPA H13 (477737)
- 1 Hose (477672)
- 1 Door airlock (477753)