

MXE 18.0-EC/5.0 Set + WR2 120

2-speed cordless mixer with 3-level speed switch 18.0 V

Order no. 495972

GTIN 4030293224520

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Large, rugged 2-gear unit with optimum ratios for powerful torque and correct speed for different materials
- + Comfortable 3-level switch can be reached from the grip position without interrupting work, protected by a rubber sleeve. Level 1: cleaning, level 2: stirring up, level 3: mixing
- + Rotary switch to set the optimum mixing speed. Speed 1: for highly viscous materials, speed 2: for medium and low viscosity materials
- + Accelerator switch for a slow and gentle start
- + On/off switch with lock and protection
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + Patented spindle lock with start-up protection. For tool-less exchange of the mixing paddle
- + For mixed applications up to 30 kg
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...
- + FLEX battery system: suitable for all FLEX 18 V battery packs



Technical data

| | |
|------------------------------|---------------------|
| Battery voltage | 18,0 V |
| Battery capacity | 2,5 / 5,0 / 8,0 Ah |
| Max. mixing basket diameter | 120 mm |
| Tool holder, mixer | M14 |
| No-load speed, 1st gear | 0 - 210/325/530 rpm |
| No-load speed, 2nd gear | 0 - 320/490/780 rpm |
| Clamping collar diameter | 53 mm |
| Number of supplied batteries | 2 Cont. |
| With charger | Yes |
| Dimensions WxLxH | 355 x 230 x 320 mm |
| Weight without battery pack | 4,1 kg |

Standard equipment

- 1 Helix paddle WR2 (368881)
- 1 Open-ended wrench SW 22 (439975)
- 1 Rapid charger (417882)
- 2 Li-Ion rechargeable battery pack 18,0 V (532733)