

ORE 3-150 EC

Powerful random-orbit sander with speed control, 150 mm

Order no. 447684

GTIN 4030293197299



- + 150 mm handy random-orbit sander with the best ergonomics and special balancing system for low-vibration operation. Provides comfortable and joint-friendly working conditions
- + Brushless motor with greater efficiency and a longer service life
- + Material-compatible sanding speed by adjustable speed
- + Effective dust extraction thanks to integrated extractor for dust-free working with filter cartridge
- + Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- + External dust extraction Ø 27 mm, adapter SAD-C 27 AS or antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- + Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- + PES filter cartridge for dust-free and efficient working
- + Velcro backing pad available in three degrees of hardness: ultra-soft, soft and hard
- + Velcro backing pad with multi-hose system for optimum extraction, suited to all standard 150 diameter abrasives
- + Especially suitable for overhead work



Technical data

Power consumption	400 W
Voltage	230 V
Frequency	50/60 Hz
Backing pad diameter	150 mm
Stroke	3 mm
No-load speed	4000 - 10000 rpm
Orbit rate, no load	8000 - 20000 rpm
Diameter dust extraction connection	Ø 27
Cable length	4,0 m
Dimensions WxLxH	230 x 150 x 125 mm
Weight	1,4 kg

Standard equipment

- 1 Hook-and-loop sanding pad medium (464120)
- 1 PES microfilter cartridge (486833)
- 1 Hexagon socket wrench (392731)