

ID 1/4" 18-EC HD2 C

Cordless impact wrench 18 V with bit ejector

Order no. 535167

GTIN 4030293290075



- + Extremely high speed and torque enable efficient work
- + Its compact and lightweight design makes it ideal for screwdriving in confined spaces
- + Tap mode for self-tapping screws in sheet metal parts with a high-quality finish. This prevents screws from being overtightened and damaging the surface. Two adjustment options for thin and thick sheet metal parts
- + With bit ejector for quick and easy bit change
- + 360° LED ring light on the head for optimum illumination of the work area, dimmable, adjustable to 5 brightness levels
- + Speed Command: three different speed settings for a variety of applications. Prevents, among others, over tightening of small screws
- + Brushless motor with greater efficiency and a longer service life
- + 1/4" hex tool holder
- + Electronic quick-acting brake
- + Right/left rotation with safety catch
- + Robust gearbox housing made of die-cast aluminium with protective heat-resisting cap
- + Ergonomically designed, non-slip, soft grip handle
- + Including belt clip and bit storage
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

Battery voltage	18 V
Battery capacity	2.5 / 4.0 / 5.0 / 8.0 Ah
Torque settings	3 Steps
Max. torque, setting 1	70 Nm
Max. torque, setting 2	100 Nm
Max. torque, setting 3	240 Nm
No-load speed	0 - 4100 rpm
No-load speed, 1st gear	0 - 1500 rpm
No-load speed, 2nd gear	0 - 2000 rpm
No-load speed, 3rd gear	0 - 4100 rpm
No-load blows	0 - 4550 1 rpm
No-load blows, setting 1	0 - 3000 1 rpm
No-load blows, setting 2	0 - 4000 1 rpm
No-load blows, setting 3	0 - 4550 1 rpm
Tool holder, impact drill	1/4" inside
Dimensions WxLxH	114 x 76 x 208 mm
Weight without battery pack	1.1 kg

Standard equipment

- 1 Bit storage
- 1 Belt clip

www.flex-tools.com

this is proformance **FLEX**