

TS 92 18-EC

Cordless benchtop circular saw 18 V

Order no. 532591

GTIN 4030293264311



- + Cutting capacity of 92 mm with the saw blade measuring just 254 mm. The cutting height can be adjusted easily and precisely using the handwheel
- + Extremely lightweight cordless table saw for maximum mobility on the construction site. Can be fixed to the folding base frame without tools (optionally available as an accessory)
- + Angle stop with long guide profile and fine adjustment, adjustable from from 0° to 60° with detent points. For mitre cuts up to 480 mm
- + Continuous angle adjustment for mitre cuts from 0-45°
- + Work with the right material at the right speed. The set speed preselection is adopted as a constant speed. The result is better cutting quality and a longer saw blade service life
- + 18 V EC motor with overload protection and temperature monitoring
- + Brushless motor with greater efficiency and a longer service life
- + Comfortable working with CutSense - Auto Mode, the sensor stops the motor after cutting
- + LED lamp integrated in the parallel fence for optimum illumination of the work area. Rechargeable with USB-C
- + High-precision parallel fence with rack and pinion system. Supports longitudinal cuts up to 427 mm on the left side and 780 mm on the right side. Very smooth and quick adjustment
- + All attachments such as angle and parallel fence, push stick, protective cover, anti-kickback device, tool spanner and Allen key can be stowed under the table for transport
- + Connector for external dust extraction Ø 27, 36 mm
- + Woodshaving collection bag for low-dust operation, simple to empty
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

Dimensions WxLxH	706 x 695 x 346 mm
Weight	23 kg
Battery capacity	5,0 / 8,0 Ah
Battery voltage	18 V
No-load speed	2000 / 2600 / 3200 / 3800 / 4400 / 5000 rpm
Max. longitudinal cut left	427 mm
Max. longitudinal cut right	780 mm
Cutting depth, mitre cut (45°)	58 mm
Cutting depth	92 mm
Max. cutting width, angle stop	480 mm
Table size, width	560 mm
Table size, length	702 mm
Angle setting, stop	60° - 0° - 60°
Angle preset	0 / 45°

Standard equipment

- 1 Standard circular saw blade with alternating teeth (532673)
- 1 Adapter (461636)
- 1 Extraction adapter
- 1 Dust bag
- 1 Parallel stop
- 1 Angle stop
- 1 Push stick
- 1 Disc guard
- 1 Splitting wedge
- 1 Anti-kickback device
- 1 Hexagon socket wrench, SW 5
- 1 Spanner