




ODE 2-100 18-EC/2.5 S

18 V cordless delta sander with speed control Order no. 532089 GTIN 4030293259294



- 😝 Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- Sanding speed suitable for the material thanks to electronic speed adjust-
- E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- Hook & loop backing pad with 10-hole system for optimum extraction, suitable for all standard abrasives
- ♠ External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- 1 Integrated dust extraction with dust filter bag
- 3 Brushless motor with greater efficiency and a longer service life
- Electronics: Speed preselection with 4 settings
- 😝 Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- LED battery capacity display
- ♣ FLEX battery system: suitable for FLEX 18,0 V/5,0/2,5 Ah battery packs











Technical data

Battery voltage	18 V
Battery capacity	2.5 / 5.0 Ah
Stroke	2 mm
No-load speed	6000 - 10000 rpm
Orbit rate, no load	12000 - 20000 rpm
Backing pad width	100 mm
Backing pad length	150 mm
Diameter dust extraction connection	Ø 27
Dimensions WxLxH	228 x 100 x 140 mm
Weight without battery pack	1.0 kg

Standard equipment

- 1 Adapter, short (532094)
- 1 Adapter, long (532095)
- 2 Li-lon rechargeable battery pack 18 V (532732) 1 Carrying case L-BOXX® (414093)
- 1 Case insert (532882)
- 1 Rapid charger 12/18 V (532280)