

OSE 2-80 18-EC C

18 V cordless orbital sander with speed control

Order no. 532084

GTIN 4030293259249



- + Lightweight, compact one-handed orbital sander, very ergonomic and low-vibration thanks to special balancing for fatigue-free and joint-friendly work
- + Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- + Sanding speed suitable for the material thanks to electronic speed adjustment
- + E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- + Hook & loop backing pad with 12-hole system for optimum extraction, suitable for all standard abrasives
- + External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- + Integrated dust extraction with dust filter bag
- + Brushless motor with greater efficiency and a longer service life
- + Electronics: Speed preselection with 4 settings
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + LED battery capacity display
- + FLEX battery system: suitable for FLEX 18,0 V/5,0/2,5 Ah battery packs. Delivery does not include battery and charger



Technical data

Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Stroke	2 mm
Backing pad length	133 mm
Backing pad width	80 mm
Orbit rate, no load	12000 - 20000 rpm
No-load speed	6000 - 10000 rpm
Diameter dust extraction connection	Ø 27
Dimensions WxLxH	204 x 83 x 140 mm
Weight without battery pack	1,0 kg

Standard equipment

- 1 Dust bag (532093)
- 1 Adapter, short (532094)
- 1 Adapter, long (532095)