

VCE 26 H MC

Safety vacuum cleaner with manual filter cleaning system, 25 l, class H

Order no. 519820

GTIN 4030293239104

- + Handy and compact vacuum cleaner, easy to use and easy to transport
- + The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result
- + By actuating manual filter cleaning, dust deposited in the filter element is removed by a targeted blast of air
- + Suitable for dry, non-flammable dusts that are harmful to the health and carcinogenic substances
- + Safety vacuum cleaner class H: suitable for all dusts with OEL values $< 0.1 \text{ mg/m}^3$
- + Ideal to remove mould, restore roofs and walls insulated with mineral wool. Sanding dust from wooden surfaces that have been impregnated with hazardous wood preservatives and from painted surfaces with paint that contains substances such as lead, nickel, cadmium, chromium, zinc chromate, etc.
- + Level monitor, no malfunctions when drawing in liquids thanks to installed float valve
- + Flow sensor technology monitors the flow rate and emits an audible signal to indicate any drop below the statutory minimum value of $\leq 20 \text{ m/s}$
- + With appliance socket and electronic automatic switch on/off
- + Soft start stops any voltage peaks at the start and the run-on feature (5 sec. overrun) empties any remaining dust in the vacuum hose
- + With accessories magazine for suction nozzles and suction tubes on the back
- + Equipped with large wheels and two swivel guide rollers
- + Dust-protected antistatic finish prevents electric charging of the suction hose
- + Has a fleece filter bag for optimum filling



Technical data

Power consumption	1200 W
Voltage	230 V
Frequency	50/60 Hz
Vacuum cleaner flow rate	3700 l/min
Max. vacuum	24500 Pa
Filter surface area	3000 cm ²
Tank volume	25 L
Liquid capacity	16 L
Suction power control	mechanical
Hose length	4m m
Number of suction motors	1 Cont.
Cable length	7,5 m
Dimensions WxLxH	475 x 377 x 526 mm
Weight	10 kg

Standard equipment

- 1 Cleaning set (445053)
- 1 Antistatic suction hose with auxiliary air control (406708)
- 1 Fleece filter bag (502235)