

# BSE 8-4 50

Burnishing machine TRINOXFLEX

Order no. 453404

GTIN 4030293201026



- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- + Variably adjustable burnishing attachment, allows working close up to the edge with narrow rollers, incl. edge guide
- + Tool-free grinding tool change via a patented quick-change system
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Adjustable guard: for sanding tools up to  $\varnothing$  125 mm
- + Spindle lock
- + For optimum finishing of various materials, for burnishing, texturing, polishing, brushing, smoothing, de-rusting and deburring steel and stainless steel surfaces



## Technical data

Power consumption	800 W
Power output	425 W
Voltage	230 V
Frequency	50/60 Hz
Brush diameter	125 mm
Brush width	50 mm
No-load speed	1400 - 4000 rpm
Tool fixture, brush sander	19mm
Cable length	4.0 m
Dimensions WxLxH	320 x 210 x 195 mm
Weight	2.3 kg

## Standard equipment

- 1 Sanding attachment, burnishing (459577)
- 1 Hexagon socket wrench (102229)