

# MXE 18.0-EC/5.0 Set + HP2 120

**2-speed cordless mixer with 3-level speed switch 18.0 V**

**Order no. 495972**

**GTIN 4030293224520**

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Large, rugged 2-gear unit with optimum ratios for powerful torque and correct speed for different materials
- + Comfortable 3-level switch can be reached from the grip position without interrupting work, protected by a rubber sleeve. Level 1: cleaning, level 2: stirring up, level 3: mixing
- + Rotary switch to set the optimum mixing speed. Speed 1: for highly viscous materials, speed 2: for medium and low viscosity materials
- + Accelerator switch for a slow and gentle start
- + On/off switch with lock and protection
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + Patented spindle lock with start-up protection. For tool-less exchange of the mixing paddle
- + For mixed applications up to 30 kg
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...
- + FLEX battery system: suitable for all FLEX 18 V battery packs



## Technical data

|                              |                     |
|------------------------------|---------------------|
| Battery voltage              | 18 V                |
| Battery capacity             | 2,5 / 5,0 / 8,0 Ah  |
| Max. mixing basket diameter  | 120 mm              |
| Tool holder, mixer           | M14                 |
| No-load speed, 1st gear      | 0 - 210/325/530 rpm |
| No-load speed, 2nd gear      | 0 - 320/490/780 rpm |
| Clamping collar diameter     | 53 mm               |
| Number of supplied batteries | 2 Cont.             |
| With charger                 | Yes                 |
| Dimensions WxLxH             | 355 x 230 x 320 mm  |
| Weight without battery pack  | 4,1 kg              |

## Standard equipment

- 1 Helix paddle HP2 (534027)
- 1 Open-ended wrench SW 22 (439975)
- 2 Li-Ion rechargeable battery pack 18 V (532733)
- 1 Rapid charger 12/18 V (532280)