this is proformance



LD 24-6 180, Kit TH-Jet

Grinding machine for large areas, 180 mm Order no. 418870 GTIN 4030293184442

- Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and flying stones
- Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- Soft-start: for a soft start without power overloading
- Restart protection after power interruption
- Extraction hood: with stepless height adjustment
- Vacuum attachment: 32 mm exterior Ø
- Spindle lock
- Ideal for large areas
- Optimum guidance by rear shaft handle
- With steplessly adjustable, vibration-proof, ergonomic bail handle, for optimum handling and machine control
- Suction hose/adapter not included in delivery package
- Sanding plates of heights 22 mm to 28 mm are suitable
- Diamond grinding disc suitable for grinding concrete parts, roughing old weathered concrete, hard cement plaster, removing shuttering protrusions and concrete runs, hardened epoxy resin coatings and the natural sintering on concrete components. High grinding capacity and service life from the innovative segment design. Optimal ground preparation for further coating.





Technical data

Power consumption	2400 W
Power output	1450 W
Voltage	230 V
Frequency	50/60 Hz
Disc diameter	180 mm
No-load speed	6500 rpm
Tool holder, renovation grinder	M14
Cable length	4.0 m
Dimensions WxLxH	570 x 240 x 140 mm
Weight	6.6 kg

Standard equipment

- 1 Thermo-Jet diamond grinding disc (359386)
- 1 Guard with rubber extraction ring (421154)
- 1 Adapter (445142)
- 1 Clamping nut M 14 (100080)
- 1 Clamping flange, SW 17 (191604)
- 3 Cable clip (302538)
- 1 Hexagon socket wrench, SW 6 (256832)
- 1 Face pin spanner (392537)
- 1 Carrying case (444391)
- 1 Bail handle