

# RFE 40 18.0-EC

Cordless gutter bracket slot cutter 18.0 V

Order no. 521582

GTIN 4030293239890



- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Electronics: Speed preselection with 4 settings, constant speed control by means of tachogenerator, overload protection, restart lock, temperature monitoring and anti-kickback function
- + 4 HSS reversible cutters: the cutters can be reversed, allowing them to be used four times
- + Plane width 40 mm, controlled chip channelling
- + On/Off switch with dead-man function
- + Adjustable to 6 mm and 8 mm thick gutter supports
- + Perfect dust protection thanks to removable protective metal grille
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



## Technical data

Battery voltage	18 V
Battery capacity	2.5 / 5.0 / 8.0 Ah
No-load speed	3800 - 6200 rpm
Planing width	40 mm
Planing depth	6/8 mm
Weight without battery pack	2.96 kg

## Standard equipment

- 1 HSS reversible blades (241091)
- 1 Torx wrench (258861)
- 1 Open-ended wrench SW 17 (106461)
- 1 Carrying case L-BOXX® (414093)
- 1 Case insert (502820)