this is proformance



MXE 1200 + HP2 140

1200 watt 1-speed mixer with 3-level speed switch

Order no. 495913 GTIN 4030293224476

- Large, rugged single-speed gear unit with optimum gear ratio for high torque
- Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- Comfortable 3-level switch can be reached from the grip position without interrupting work, protected by a rubber sleeve. Level 1: cleaning, level 2: stirring up, level 3: mixing
- On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- Spindle lock with start-up protection. Simplifies exchange of the mixing paddle
- For mixed applications up to 60 kg
- With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...

















Technical data

io cilii cai aata	
Power consumption	1200 W
Power output	710 W
Voltage	230 V
Frequency	50/60 Hz
Max. mixing basket diameter	140 mm
Tool holder, mixer	M14
No-load speed, 1st gear	0 - 210/325/530 rpm
Clamping collar diameter	53 mm
Cable length	4,0 m
Dimensions WxLxH	405 x 215 x 340 mm
Weight	4,6 kg

Standard equipment

- 1 Open-ended wrench SW 22 (439975)
- 1 Helix paddle HP2 (534028)