

JS 18.0-EC C


Cordless jigsaw 18.0 V

Order no. 485403

GTIN 4030293217836



- + New generation of brushless motors delivering high efficiency and performance
- + Continuously variable cutting speed setting via potentiometer wheel with automatic start-up in position A
- + Electronic switch can be operated from both sides
- + Tool-free saw blade change with quick-clamping system and eject function
- + Orbital stroke: 4 settings for higher cutting rate
- + Double roller jigsaw blade guide for precise cuts with accurate angles
- + Free view of the marking thanks to integrated blow function
- + Perfect ergonomics thanks to ideally located SoftGrip surfaces
- + Low-vibration and comfortable sawing
- + Saw bench adjustment for bevel cuts of up to 45°, 0-lock. Can be set off backwards for sawing close to edges
- + Stable base plate with removable plastic guide block for the protection of delicate surfaces
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + With automatic start-up, overload protection
- + Vacuum flange Ø 27 mm, for a cleaner workplace and clear view of the cut
- + Removable chip screen, for tear-free cuts and for guiding the saw blade
- + Integrated LED lamp for optimum illumination of the work area.
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

| | |
|--------------------------------|--------------------|
| Battery voltage | 18 V |
| Battery capacity | 2.5 / 5.0 / 8.0 Ah |
| Orbit rate, no load | 0 - 3500 rpm |
| Stroke | 26 mm |
| Pendulum stroke stages | 4 Steps |
| Speed settings | 1-5 +A Steps |
| Pivoting range | 0-45° |
| Max. material thickness, wood | 120 mm |
| Max. material thickness, metal | 8 mm |
| Dimensions WxLxH | 275 x 82 x 197 mm |
| Weight without battery pack | 2.1 kg |

Standard equipment

- 1 Sliding shoe (490237)
- 1 Hexagon socket wrench (102229)
- 1 Anti-splinter guard (490229)
- 1 Adapter (490245)
- 1 Protection against flying swarf, closed