

# DD 2G 18-EC HD2 C

2-speed cordless drill driver 18 V with turbo mode

Order no. 535165

GTIN 4030293290051



- + Brushless motor with greater efficiency and a longer service life
- + Highest torque of 170 Nm for drilling and screwdriving even in extreme applications
- + With switchable anti-kickback function, for constant power transmission without unwanted interruption. Useful for metal work such as thread cutting, step drilling or core drilling
- + Anti-kickback, switches off the motor in case of jamming to prevent the wrist from twisting
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Robust gearbox housing made of die-cast aluminium
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + Including attachable auxiliary handle, belt clip and bit storage
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



## Technical data

|                                 |                       |
|---------------------------------|-----------------------|
| Battery voltage                 | 18 V                  |
| Battery capacity                | 2.5 / 5.0 / 8.0 Ah    |
| No-load speed, 1st gear         | 0 - 700 rpm           |
| No-load speed, 2nd gear         | 0 - 3000 rpm          |
| Max. torque, hard               | 170 Nm                |
| Max. drilling diameter in wood  | 160 mm                |
| Max. drilling diameter in steel | 13 mm                 |
| Chuck clamping width            | 1,5-13 mm             |
| Dimensions WxLxH                | 173 x 65 x 214 mm     |
| Weight without battery pack     | 1.6 kg                |
| Torque adjustment               | 22+1 Steps            |
| Sound pressure level            | 77 dB(A)              |
| Vibration                       | <2.5 m/s <sup>2</sup> |

## Standard equipment

1 Belt clip  
1 Handle  
1 Bit storage

