

this is proformance

Making everything



Polishing and Automotive Products



3-year warranty* Simply register and get started. https://warranty.flex-tools.com * Applies to battery packs and chargers too.

So that it's all as good







Three things are needed for the perfect surface finish: skill, the right feel, and FLEX, of course. Whether you are a professional working in a paint shop, an automotive all-rounder or a detailer - FLEX allows everyone to shine with the optimum system of polisher, pad and polish. The right combination is particularly important, because with the correct components to suit your experience, the material and the condition of the paintwork, you are certain to achieve brilliant results.

System with in-built safety

The right combination for perfect surfaces



Polisher

There are good reasons why FLEX polishers are the first choice of the professionals. FLEX has been defining the high technological standard for premium polishers for more than 90 years and thus has unique know-how which ensures our tools are noticeably better.



Pad

The optimum result is achieved only with the correct choice of polishing medium. The user must be familiar with the different effects produced by foams or fibre-based products such as fleece, wool and microfibre pads if they are to achieve the desired abrasive effect. The FLEX pads with colour-coded system provide clear quidance here.



Polish

The FLEX system is rounded off with perfectly coordinated abrasive, finishing and sealing polishes. They are the perfect match for our system and are silicone-free, of course.

Achieve your goal with the correct drive

0

18V


Experience and task determine the technology needed

FLEX provides the whole range of drive technologies for polishers and thus solutions for all types of user, be they a professional or a beginner with little experience. As a matter of principle: rotary polishers achieve a high removal rate and thus belong in experienced hands only because the workpiece usually requires subsequent finishing with a random orbital polisher.

Drive


Properties

Rotary



🔊 Highest removal rate


- Rotary polishers require experience
- Quickest way to remove scratches
- **7** Hologram formation possible



Random orbital, with positive-action drive




- 🔊 Good removal performance
- No hologram formation
- Suitable for removing scratches and for finishing
- Wide range of applications



Random orbital, free-running



- Suitable for all types of user
- Easy to handle
- 🔊 No hologram formation
- Poor removal performance
- 🔊 Ideal for finishing



1 Time required to remove damage 2) Risk of hologram formation

Rotary polisher

Great performance great remova



PE 14-2 150

The high-end polisher for professional car restoration. Perfect speed range plus high torque.

Technical features

- Microprocessor electronics: continuously adjustable speed selection, tachometer-controlled constant speed, overload protection, restart protection and temperature monitoring
- Powerful 1,400-watt motor with powerful fan for optimum cooling
- Accelerator trigger switch for a slow and gentle start (starting speed at setting 1 (380 rpm)) and lock for continuous operation
- Optimised airflow for the best possible cooling effect of the motor and gearbox. No exhaust air to annoy the user
- Novel combination of planetary and angle gear reduces noise to a minimum
- Flat gear head reduces the distance from the surface. This allows the tool to be operated correctly in any position
- Handle cover: ergonomically shaped with Soft-Grip. The tool can be guided with precision and always provides a pleasant and safe grip
- Spindle lock: is ideally positioned to avoid operating errors and not to influence the grip area
- With rubber-coated storage surface for safe storage
- 4-metre PUR H05-BQF cable: wear resistant, flexible with high abrasion and notch resistance

PE 14-2 150

Standard equipment

• 1	handle
-----	--------

•

Order No. 373680

Technical data

Max. polishing pad Ø	200 mm
Max. backing pad Ø	150 mm
No-load speed	380-2100/min
Power consumption	1400 W
Tool fixture	M 14
Weight	2.3 kg

High-end basic polisher for:

- Car restoration
- Bodywork
- Paint shop
- Car repair shop
- Smart repair
- Aviation
- A Maritime
- Furniture
- Acrylic glass



Order No.

376175



FLEX

PE 14-2 150 P-Set

Standard equipment

- 1 handle
- 1 hook and loop backing pad, cushioned Ø 150 mm
- 1 polishing wool pad TW-PT 160
- 1 microfibre cloth MW-P
- 1 case insert
- 1 polishing sponge PS-O 160
- 1 polishing sponge PS-V 160
- 1 polish P03/06-LDX 250 ml
- 1 polish P05/05-LDX 250 ml
- 1 carrying case L-BOXX[®] 238

PE 14-1 180

The specialist for large areas and heat-sensitive materials or when large polishing pads are required.

Technical features

As PE 14-2 150

- Accelerator trigger switch for a slow and gentle start (starting speed at setting 1 (250 rpm)) and lock for continuous operation
- Specially designed for polishing large horizontal and vertical surfaces. For automotive, maritime, aviation applications
- Polishes with extremely low speed and high torque, e. g. for heat-sensitive surfaces

High-end polisher for:

- Maritime
- Aviation
- Car restoration
- Furniture
- Acrylic glass




605

Technical data

FLEX III'O

Max. polishing pad Ø	250 mm
Max. backing pad Ø	180 mm
No-load speed	250-1380/min
Power consumption	1400 W
Tool fixture	M 14
Weight	2.3 kg



PE 14-1 180

Standard equipment

1 handle

Order No.	
395749	

FLEX 11

PE 8-4 80

The handy polisher for small areas. Ideal as an ancillary tool.


Technical features

- VR Electronics: with tachometer-controlled constant speed, soft start, overload protection and speed preselection
- Lightweight and handy for use on smaller areas, difficult to reach places
- Spindle lock

Ancillary polisher for

- Car restoration
- Bodywork
- Smart repair





Technical data

Max. polishing pad Ø	80 mm
Max. backing pad Ø	75 mm
No-load speed	1300-3900/min
Power consumption	800 W
Tool fixture	M 14
Weight	1.8 kg

PE 8-4 80

Standard equipment

1 side handle

Order No. 405817

PE 14-3 125

The all-rounder for small to medium-sized polishing

discs.

Technical features

- VR microprocessor electronics: with tachometer-controlled constant speed, soft start, accelerator trigger switch, restart protection after power failure, overload protection, temperature monitoring and speed preselection
- Accelerator trigger switch for a slow and sensitive start
- Thanks to the wide speed range, ideally suited to work perfectly with polishing pads from Ø 80 to max. Ø 160 mm
- Recommended polishing pad Ø 140 mm
- Ergonomic design
- Slim handle and ergonomically shaped handle cover for optimum handling and fatigue-free polishing
- 4-metre PUR H05-BQF cable: wear resistant, flexible with high abrasion and notch resistance
- Spindle lock

Ancillary polisher for

- Workshops
- Bodywork
- Paint shop
- Smart repair



Technical data

FLEX

160 mm	
125 mm	
1100-3700/min	
1400 W	
M 14	
2.2 kg	

PE 14-3 125

Standard equipment

1 side handle

Order No.

40681	3
	~

PE 14-3 125 P-Set

Standard equipment

- 1 side handle
- 1 hook and loop backing pad, Ø 125
- 1 microfibre cloth MW-PC
- 1 polishing sponge PS-O 160
- 1 polishing sponge PS-V 160
- 1 polish P03/06-LDX 250 ml
- 1 polish P05/05-LDX 250 ml

Order No. 407569 Random orbital polisher with positive-action drive

Full control during every revolution

FLEX



XCE 10-8 125

Rotary and random orbital motions combined in one polisher. For effective and efficient surface finishing.

Technical features

- VR microprocessor electronics: with tachometer-controlled constant speed, soft start, accelerator trigger switch, restart protection after power failure, overload protection, temperature monitoring and speed preselection
- 8 mm polishing stroke, positive-action drive provides high abrasive power without creating any holograms
- Cushioned special hook and loop backing pad for polishing
- Very smooth running thanks to to balancing mass
- Basic unit for hologram-free working on the most common surface problems through to finishing
- Flat gear head reduces the distance from the surface. This allows the tool to be operated correctly in any position
- Handle cover: ergonomically shaped with Soft-Grip. The tool can be guided with precision and always provides a pleasant and safe grip
- Optimised airflow for the best possible cooling effect of the motor and gearbox. No exhaust air to annoy the user
- Low heat generation on the surface makes it ideal for temperature-sensitive paints

Random orbital polisher for:

- Car restoration
- Car dealers
- Paint shop
- Car repair shop
- Smart repair
- Maritime





XCE 10-8 125

Standard equipment

• 1 special hook & loop backing pad, 125 Ø

Order No.	
418072	

Technical data

Max. polishing pad Ø	160 mm
Max. backing pad Ø	150 mm
No-load speed	140-430/min
Stroke rate at no-load	2900-8600/min
Stroke	8 mm
Power consumption	1010 W
Weight	2.6 kg

XCE 10-8 125 P-Set

Standard equipment

- 1 special hook and loop backing pad Ø 125 mm
- 1 polishing sponge PS-O 140
- 1 polishing sponge PSX-G 140
- 1 polish P03/06-LDX 250 ml
- 1 polish P05/05-LDX 250 ml
- 1 microfibre cloth MW-PC
- 1 carrying case L-BOXX[®] 238
- 1 case insert

Order No.

447269



Free-running random orbital polisher

Always in good hands

AcLaren

FLEX

IIIP



XFE 7-15 150

Ideal for beginners or when working on 2-stage processes. As a supplementary tool to the rotary polisher, it provides fast hologram removal and a perfect finish.

Technical features

- VR microprocessor electronics: with tachometer-controlled constant speed, soft start, accelerator trigger switch, restart protection after power failure, overload protection, temperature monitoring and speed preselection
- Free-running drive for hologram-free finishing
- 15 mm polishing stroke for high efficiency
- Accelerator trigger switch for a slow and sensitive start and locking for continuous running
- Cushioned special hook and loop backing pad for polishing
- Very smooth running thanks to to balancing mass
- Optimised airflow for the best possible cooling effect of the motor and gearbox.
- Flat gear head reduces the distance from the surface. This allows the tool to be operated correctly in any position
- Handle cover: ergonomically shaped with Soft-Grip.
- Low heat generation on the surface makes it ideal for temperature-sensitive paints

XFE 7-15 150

Standard equipment

- 1 special hook and loop backing pad, Ø 125
- 1 special hook and loop backing pad, Ø 150

Order No.

41	808	0
----	-----	---

Technical data

Max. polishing pad Ø	160 mm
Max. backing pad Ø	150 mm
No-load speed	1500-4500/min
Stroke rate at no-load	3000-9000/min
Stroke	15 mm
Power consumption	710 W
Weight	2.4 kg

Random orbital polisher

for:

Car restoration

- Car dealers
- Paint shop
- Car repair shop
- Smart repair
- Maritime

XFE 7-15 150 P-Set
Standard equipment

1 special hook and loop backing pad, Ø 125
1 special hook and loop backing pad, Ø 150

- 1 polishing sponge PS-O 160
- 1 polishing sponge PS-R 160
- 1 microfibre cloth MW-C
- 1 polish P03/06-LDX 250 ml
- 1 sealant W02/04 250 ml
- 1 carrying case L-BOXX[®] 238
- 1 case insert

Order No. 447110





FLEX



Note: If the original FLEX accessories are not used with the XFE/XCE models, this can lead to increased vibrations, a poorer end result or increased wear, or even cause equipment damage!



XFE 7-12 80

The small, compact tool is the ideal complement to larger polishers. Perfect for spot repairs. It can be used for a large number of applications when working with difficult shapes.

Technical features

- VR Electronics: with tachometer-controlled constant speed, soft start, overload protection, temperature monitoring and speed preselection
- Free-running drive for hologram-free finishing
- Handle cover: ergonomically shaped with Soft-Grip. The tool can be guided with precision and always provides a pleasant and safe grip
- 12 mm polishing stroke for high efficiency
- Lightweight and handy for use on smaller areas, difficult to reach places
- Low heat generation on the surface makes it ideal for temperature-sensitive paints
- Perfect for spot repairs and difficult shapes. Ideal complement to larger polishers

- Supplementary polisher for:
- Car restoration
- Car repair shop
- Smart repair
- Maritime
- Acrylic glass

XFE 7-12 80

Standard equipment

1 special hook and loop backing pad Ø 75

Order No.

Technical data

Max. polishing pad Ø	80 mm
Max. backing pad Ø	75 mm
No-load speed	1800-5500/mir
Stroke rate at no-load	3600-10800/mir
Stroke	12 mm
Power consumption	700 W
Weight	2.1 kg

XFE 7-12 80 P-Set

Standard equipment

- 1 special hook and loop backing pad Ø 75
- 1 polishing sponge PSX-G 80
- 1 polishing sponge PS-O 80
- 1 polishing sponge PS-R 80
- 1 microfibre cloth MW-PC
- 1 polish P05/05-LDX 250 ml
- 1 sealant W02/04 250 ml
- 1 carrying case L-BOXX[®] 136
- 1 case insert

Order No.

447137









FLEX is and will remain the benchmark for professional quality in the field of polishing - even with 18 V battery power. High end surface finishing then becomes as independent and flexible as never before. A matter of course: There are no compromises in terms of performance and security in the system. True proformance.



Cordless polisher - The full range

- Random orbital or rotational drive technology
- For all users from professional polishers to beginners
- For all painted surfaces in automotive, caravanning, aviation, and maritime applications
- Two exchangeable batteries for work without breaks
- For perfect results

Perfect balance

Maximum freedom of movement and ergonomics for the user. The optimum location of the battery not only perfects the spread of weight, but also promotes the polisher's high-response manoeuvrability without disruptive elements and any possible contact with the painted workpiece. Never before has the polisher been so responsive!



Powerful battery technology



Therma-Tech™ technology

Integrated cooling - The innovative thermal management allows you to work at full power for much longer.



POWER BATTERY

High-performance battery cells - The FLEX high-performance cells use the full battery capacity and thus allow longer battery runtimes!



KEEP CONTROL technology

Intelligent battery management system constant data exchange between battery pack, tool and quick charger.



EC technology means tool requires no maintenance whatsoever

- 🔊 Up to 65% longer runtime
- 🛷 Up to 10x longer service life
- 🔊 Up to 30% more power



PE 150 18.0-EC

Concentrated power with high speed for high removal rate

Technical features

- Intelligent Electronic Management
 System
- Centrally positioned speed wheel can be operated from both sides
- Spindle lock
- Ergonomic handle with SoftGrip
- Durable and powerful EC motor
- Accelerator trigger switch with lock
- Ergonomic handle cover with Soft-Grip
- M14 tool holder

Cordless rotary polisher for:

- Vehicle cleaners
- Car repair shops
- Smart repairs
- Aviation
- Maritime
- Acrylic glass industry





Technical data

Max. polishing pad Ø	160 mm
Max. backing pad Ø	150 mm
Tool holder	M14
No-load speed	150-1450/min
Battery voltage	18 V
Battery capacity	2.5 / 5.0 Ah
Average battery runtime 2.5 Ah	up to 15 min
Average battery runtime 5.0 Ah	up to 35 min
Weight excluding battery	1.9 kg
Weight with 5.0 Ah battery	2.7 kg

PE 150 18.0-EC C

Supplied in a box

Standard equipment

- 1 hook and loop backing pad, Ø 150 mm
- 1 handle

Order No.

493856

PE 150 18.0-EC

Standard equipment

- 1 hook and loop backing pad, Ø 150 mm
- 1 handle
- 1 carrying case
 L-BOXX[®] 238
- 1 case insert

Order No.

459062

		1.0	There a	
1.00				0
1	-		-	- 0
1				
ų				-

PE 150 18.0-EC/5.0 Set

Standard equipment

- 1 hook and loop backing pad, Ø 150 mm
- 1 handle
- 2 rechargeable batteries 5.0 Ah AP 18.0/5.0
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX[®] 238
- 1 case insert

Order No.

447153



PE 150 18.0-EC/5.0 P-Set

Standard equipment

- 1 polishing sponge PS-0 160
- 1 polishing sponge PS-V 160
- 1 polishing wool pad TW-PT 160
- 1 polish P03/06-LDX 250 ml
- 1 polish P05/05-LDX 250 ml
- 1 microfibre cloth MW-P
- 1 hook and loop backing pad, Ø 150 mm
- 1 handle
- 2 rechargeable batteries 5.0 Ah
- AP 18.0/5.0

 1 charger
- CA 10.8/18.0
- 1 carrying case
 L-BOXX[®] 238
- 1 case insert

Order No. 461229



19

Free-running cordless eccentric polisher

Carefully forwards



XFE 15 150 18.0-EC

Random orbital polishers remove material gently for reliable results.

That makes them ideal for beginners.

Technical features

- Electronic management system (EMS) protects the tool, extends its service life and increases efficiency
- Brushless motor with greater efficiency and a longer service life
- LED battery capacity capacity indicator
- Free-running drive for hologram-free finishing
- 15 mm polishing stroke for high efficiency
- Accelerator trigger switch for a slow and sensitive start
- Cushioned special hook and loop backing pad for polishing
- Very smooth running thanks to to balancing mass
- Flat gear head reduces the distance from the surface.
- Handle cover: ergonomically shaped with SoftGrip.
- Low heat generation on the surface makes it ideal for temperature-sensitive paints

XFE 15 150 18.0-EC C

Supplied in a box

- **Standard equipment**
- Special hook and loop
 - 1 backing pad Ø 125 mm
- 1 backing pad Ø 150 mm Order No.

493864

XFE 15 150 18.0-EC

Standard equipment

- 1 special hook and loop backing pad Ø 125 mm
- 1 special hook and loop backing pad Ø 150 mm
- 1 carrying case L-BOXX® 238
- 1 case insert
- Order No.

459089

Cordless eccentric polisher for:

- Vehicle cleaners
- Car repair shops
- Smart repairs
- Aviation
- Car dealers
- A Maritime
- Acrylic glass industry



XFE 15 150 18.0-EC/5.0 Set

Standard equipment

- · 1 special hook and loop backing pad Ø 125 mm
- 1 special hook and loop backing pad Ø 150 mm
- · 2 rechargeable batteries 5.0 Ah AP 18.0/5.0
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX[®] 238
- 1 case insert



Order No. 418099



Slia

Technical data

Max. polishing pad Ø	160 mm
Max. backing pad Ø	150 mm
Stroke	15 mm
No-load speed	2300-3800/min
Stroke rate at no-load	4600-7600/min
Battery voltage	18 V
Battery capacity	2.5 / 5.0 Ah
Average battery runtime 2.5 Ah	up to 20 min
Average battery runtime 5.0 Ah	up to 45 min
Weight excluding battery	2.1 kg
Weight with 5.0 Ah battery	2.8 kg

XFE 15 150 18.0-EC/5.0 P-Set

Standard equipment

- Special hook and loop 1 backing pad Ø 125 mm 1 backing pad Ø 150 mm
- 1 polish P03/06-LDX 250 ml
- 1 sealant W02/04 250 ml
- 1 microfibre cloth MW-PC
- 1 polishing sponge PS-0 160
- 1 polishing sponge PS-R 160
- · 2 rechargeable batteries 5.0 Ah AP 18.0/5.0
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX® 238
- 1 case insert Order No.


461237





Cordless random orbital / rotary polishers

Master of the quick change





Can be converted in just 10 seconds - no tools, no stress.



FL

THE YEAR

PXE 80 10.8-EC

The all-rounders for spot repairs and vehicle preparation is up to any task, from blossom sanding to hologram-free finishing.

Technical features

- Brushless motor
- Electronic Management System (EMS)
- Innovative quick-change system for exchanging the rotary and eccentric drive types without using tools
- For rotary and random orbital free-running working with 3 and 12 mm stroke
- Flexible and easy as never before from blossom sanding to hologram-free finishing with one unit
- Accelerator trigger switch for a slow and sensitive start and locking for continuous running
- With constant speed control and 4 speed levels, display easily recognisable by LEDs
- Very smooth running thanks to vibration optimisation
- Cushioned special hook and loop backing pad
- With impact protection ring to protect surfaces
- The ideal complementary tool for every vehicle refurbisher, painter and the spot repair trade.

PXE 80 10.8-EC

Supplied in a box

Order No.	
469068	

PXE 80 10.8-EC/2.5 Set

Standard equipment

- 1 adapter, rotary DT-P
- 1 random-orbital adapter, 3 mm stroke DT-XF3
- 1 random-orbital adapter, 12 mm stroke DT-XF12
- 1 adhesive pad 30 Ø BP-M/SR D30 PXE
- 1 hook & loop backing pad 30 Ø BP-M D30 PXE
- 1 hook & loop backing pad 75 Ø BP-M D75 PXE
- 2 rechargeable batteries 2.5 Ah AP 10.8/2.5
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX[®] 136
- 1 case insert



Order No.

418102

Cordless eccentric polisher

- for:
- Vehicle cleaners
- Smart repairs
- Paint shop
- Car body shops
- Car repair shops

Technical data

Max. polishing pad Ø	80 mm
Max. backing pad Ø	75 mm
Stroke	3 + 12 mm
No-load speed	400-2000/-3000/-4000/-5800/min
Stroke rate at no-load	800-4000/-6000/-8000/-11600/min
Battery voltage	10.8 V
Battery capacity	2.5 / 4.0 / 6.0 Ah
Weight excluding battery	0.63 kg

PXE 80 10.8-EC/2.5 P-Set

Standard equipment

- 1 adapter, rotary DT-P
- 1 random-orbital adapter, 3 mm stroke DT-XF3
- 1 random-orbital adapter, 12 mm stroke DT-XF12
- 1 adhesive pad 30 Ø BP-M/SR D30 PXE
- 1 hook & loop backing pad 30 Ø BP-M D30 PXE
- 1 hook & loop backing pad 75 Ø BP-M D75 PXE
- 2 polishing sponges PSX-G 40
- 2 polishing sponges PS-V 40
- 2 polishing sponges PS-V 60
- 2 polishing sponges PS-O 60
- 2 polishing sponges PS-R 80
- 1 microfibre cloth MW-PC
- 1 polish P03/06-LDX 250 ml
- 1 polish P05/05-LDX 250 ml
- 2 rechargeable batteries 2.5 Ah AP 10.8/2.5
- 1 charger CA 10.8/18.0
 1 carrying case
- L-BOXX[®] 136
- 1 case insert

Order No. 469076






























Flexible shaft FS 140

New, clever and quickly ready for use without tools. Working on spots in tricky places has never been so easy. The 140 cm shaft makes using it flexible and ideal in hard-to-reach areas.

Technical features

- Toolless mounting on PXE. The innovative quick-change mechanism of the PXE allows the shaft to be mounted quickly and easily
- Toolless quick change of accessories thanks to bit holder. This allows the polishing discs to be changed quickly and easily.
- The form fit of the hexagonal mount prevents the polishing bodies from slipping through. This guarantees even and perfect polishing results every time.
- The 140 cm shaft can be guided comfortably and conveniently without the polisher tipping or having to be held in the hand all the time.
- High-quality materials guarantee an extremely long service life.

Applications

- Paint preparation & scratch removal
- Door handle recesses and radiator grille
- Exterior mirror casing
- Vehicle emblems, logos & lettering
- Rims
- Spot repair
- Interior (piano lacquer, fittings etc.)

FS 140

Standard equipment

• 1 FS 140 in a box


DesignationOrder No.FS 140506605

FS 140 Set

Standard equipment

- 1 FS 140
- 6 polishing cones (2 each in soft, medium and hard)
- 6 polishing cylinders (2 each in soft, medium and hard)
- 1 deep-drawn insert
- 1 L-Boxx (TK-L 102)

Designation	Order No.	
FS 140 Set	516112	





Polishing cylinders

• e.g. for mouldings, spot repairs etc.

PZ-G 35 HEX VE5	517755
PZ-V 35 HEX VE5	517763
PZ-O 35 HEX VE5	517771
	PZ-V 35 HEX VE5

Polishing cones

• e.g. for door handle recesses, radiator grille, rims, interior etc.

Product variants		Order No.
Green	PK-G 35 HEX VE5	517798
Purple	PK-V 35 HEX VE5	517801
Orange	PK-O 35 HEX VE5	517828

Cordless random orbital polisher with positive-action drive

100

haximum icecom of movement





FLEX

XCE 8 125 18.0-EC

For hologram-free removal of various types of paint damage. The ideal complement for anyone who needs a portable random orbital polisher.

Technical features

- Electronic Management System (EMS)
- Brushless motor
- LED battery capacity capacity indicator
- 8 mm polishing stroke, positive-action drive provides high abrasive power without creating any holograms
- Cushioned special hook and loop backing pad
- Very smooth running thanks to to balancing mass
- Ideal for tackling the most common surface problems through to finishing without creating any holograms
- Flat gear head reduces the distance from the surface
- Handle cover: ergonomically shaped with SoftGrip.
- Optimised airflow for the best possible cooling effect of the motor and gearbox. No exhaust air to annoy the user
- Low heat generation on the surface makes it ideal for temperature-sensitive paints

XCE 8 125 18.0-EC C

Supplied in a box **Standard equipment**

 1 special hook and loop backing pad, Ø 125 mm

Order No.

493872

XCE 8 125 18.0-EC

Standard equipment

- 1 special hook and loop backing pad, Ø 125 mm
- 1 carrying case L-BOXX® 238
- 1 case insert

Order No. 459070

XCE 8 125 18.0-EC/5.0 Set

Standard equipment


- 1 special hook and loop backing pad, Ø 125 mm
- · 2 rechargeable batteries 5.0 Ah AP 18.0/5.0
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX[®] 238
- 1 case insert



Order No. 438413

Cordless eccentric polisher for:

- Over the second seco
- Car repair shops
- Smart repairs
- Aviation
- Car dealers
- O Maritime
- Acrylic glass industry



XCE 8 125 18.0-EC/5.0 P-Set

Standard equipment

Weight excluding battery

Weight with 5.0 Ah battery

- 1 polishing sponge PS-0 140
- 1 polishing sponge PSX-G 140
- 1 polish P03/06-LDX 250 ml
- 1 polish P05/05-LDX 250 ml
- 1 microfibre cloth MW-PC
- · 1 special hook and loop backing pad, Ø 125 mm
- 2 rechargeable batteries 5.0 Ah AP 18.0/5.0
- 1 charger CA 10.8/18.0
- 1 carrying case L-BOXX® 238
- 1 case insert

Order No. 461245



160 mm

150 mm

280-430/min

2.5 / 5.0 Ah

up to 20 min

up to 45 min

2.1 kg

2.8 kg

5600-8600/min

8 mm

18 V

System with in-built safety

Polish and pad play a crucial role in the polishing process. FLEX therefore provides a perfectly coordinated system with an optimum range of sponges for every application: simply use the correct colour to successfully achieve your goal.



Abrasive paste P 05/05-LDX

High removal rate with maximum sheen

The universal high-performance abrasive paste removes P1500 grit abrasion marks in seconds.

- · Suitable for all types of paint
- Contains no wax, silicone, or odorous solvents
- · For use with rotary and random orbital polishers
- Abrasiveness 5
- Gloss level 5

Order No. 443271



Special polish P 03/06-LDX

Scratch removal with a deep sheen

Ideal for polishing P2000 grit abrasion marks and for reviving old paintwork.

- Suitable for all types of paint
- Low-dust and silicone-free polish
- For single-stage random orbital polishing or rotary polishing
- Abrasiveness 3 Gloss level 6

Order No.

443298




Sealant W 02/04

Liquid preservation

Perfect paintwork protection with Carnauba wax

- For new or freshly polished paintwork
- Can be painted over
- · Contains no abrasive particles
- · Protects, cares for and maintains high sheen
- Can be applied with the red manual applicator sponge or with the orange sponge
- and a polisher. Protective effect 2 Smoothness 4

Order No. 443301















For more accessories, visit www.flex-tools.com

Sponge types	Cutting Power	Designation Ø sizes	Order No.
Green sponge - PSX-G A very hard, reticulated foam with an innovative X-Cut surface that guarant tees a uniform and very high removal rate even when used with the rando orbital polisher. The X-Cut texture also reduces heat generation. The foan heat resistant, tear resistant, and has a very good service life.	om	PSX-G 40 VE2 PSX-G 60 VE2 PSX-G 80 VE2 PSX-G 140 PSX-G 160 PSX-G 200	442631 492434 434264 434272 434280 434299
Violet sponge - PS-V A hard, reticulated foam for optimum cooling and with a constant and hig removal rate. It is slightly less abrasive than the green sponge PSX-G and is ideal for fresh coats of paint. The foam is heat resistant, tear resistant ar has a good service life.		PS-V 40 VE2 PS-V 60 VE2 PS-V 80 VE2 PS-V 140 PS-V 160 PS-V 200	442658 492442 434442 434450 434469 436410
Orange sponge - PS-O A medium-hard, reticulated foam with a fine foam texture. It is heat resistant, very tear resistant and has a good service life.		PS-O 40 VE2 PS-O 60 VE2 PS-O 80 VE2 PS-O 140 PS-O 160 PS-O 200	442666 492450 434302 434310 434329 434337
Red sponge - PS-R A very soft, reticulated foam with a fine foam texture. It has a special Per- fectTouch sandwich structure with an additional, firmer, white foam layer which gives the pad greater rigidity. This special structure also increases to service life of the polishing pad.	the	PS-R 40 VE2 PS-R 80 VE2 PS-R 140 PS-R 160 PS-R 200	442674 434345 434353 434361 434426
Blue sponge - Microfibre polishing pad MC-PT 160 Especially for random orbital polishers, particularly those with a free-run- ning pad. With these machines, a microfibre pad is more effective than a standard fleece pad for heavy cutting work. The microfibre pad is also equipped with the tried-and-tested PerfectTouch sandwich surface. This es sures good pressure distribution without softening the orbital movement	en-	MC-PT 160	434434
White pad - Wool polishing pad TW-PT TopWool Pad made from 90% natural wool and 10% polyester. This com- bination gives it a longer service life and more volume. The special Per- fectTouch structure with the additional layer of orange foam gives the par gentle cushioning and greater rigidity.		TW-PT 80 TW-PT 140 TW-PT 160	420484 376515 376523
Small red sponge - manual application sponge PUK-R 130 This sponge has an ergonomic shape and a very soft, reticulated foam with a fine foam texture. It is perfect for the manual application of sealants and care products to painted and plastic surfaces. An ideal supplement for difficult to reach places or sensitive surfaces that are difficult to treat with a to for example.	d	PUK-R 130	442682

The right choice

FLEX gives you an overview. So that application, tool and accessories produce the perfect result.


Rotary	
Random orbital, with positive- action drive	
Random orbital, free-running	
Rotary	
Random orbital, with positive- action drive	

Random orbital, free-running



For more accessories, visit www.flex-tools.com


Damage



Fields of application of the drive types



Fields of application of the pads and polishes



Automotive products

Automotive products Everything for the works op

Ξ

FLEX

DWL 2500 10.8/18.0

Powerful LED full-spectrum light with max. 3000 lumen and extremely long runtime of up to 30 hours (300 lm).

Technical features

- With Bluetooth app for lighting control for up to 4 lights and brightness setting in 5 stages
- The all-daylight function allows the colour temperature to be set in 5 stages between 2500 K - 6500 K. This enables an accurate adjustment to the job in hand
- Ideal for checking the paint surface, determining colour and detecting paintwork mistakes, holograms, scratches
- Integrated powerbank, USB port and charging option for smartphones, tablets
- Robust and durable for the most exacting demands
- Connecting thread for tripods
- LED battery capacity capacity indicator

SF 150-P Swirl Finder

Ideal LED light to control surface conditions.

Due to the colour temperature and reproduction, surface damage such as holograms, scratches etc. can be made more visible. Light intensity 140 lumens and adjustable focus with a beam angle of 10° -70°, lighting time approx. 2 hours incl. batteries.



DWL 2500 10.8/18.0

Order No. 486728

CI 11 18.0 / 12V

Cordless compressor 12.0 / 18.0 V

Technical features

- Pressure presetting with automatic switch-off when the desired pressure is reached
- Perfect flexibility thanks to 18 V battery power and 12 V on-board voltage via cigarette adapter. For filling car and bicycle tyres





Order No. 463302



Order No. 506648

BW 18.0-EC

Cordless fan / leaf blower 18.0 V

Technical features

- 18 V battery power, perfect for drying painted surfaces
- Ideal for hard-to-reach places thanks to compact design





Order No.	
472913	

33





Google pla

DWL with ease from



Accessories



Magnetic holder WB-M/DWL

Order No. 491195

VC 6 L MC

Compact vacuum cleaner with manual filter cleaning, 6 l, class L

Technical features

- Small, compact, mega power the small vacuum cleaner with cable
- Very compact, handy and light vacuum cleaner with carrying strap for portable use. The compact design means it fits in all vehicles



Order No.

481513

ORE 3-150 EC / ORE 5-150 EC

Powerful random orbital sander with speed control, 150 mm

Technical features

- Sanding speed suitable for the material thanks to adjustable speed
- Impact-resistant filter cartridge with replaceable PES filter allows easy dust disposal or cleaning of the filter with maximum service life
- Tools also available in L-BOXX[®]

ORE 3-150 EC

Order No.	
447684	

RD 10.8/18.0/230

Digital cordless construction site radio 10.8 / 18.0 V

Technical features

- Cordless construction site radio with mega sound and LED light strips
- With integrated Bluetooth[®] technology, AUX input,
 USB port and charging option for smartphones, tablets

VC 6 L MC 18.0

Compact vacuum cleaner with manual filter cleaning, 6 l, class L

Technical features

- Small, compact, mobile with powerful 18 V battery power
- Perfect for professional cleaning of vehicles, workshops, warehouses, final assembly, offices, etc.



Battery pack not included

Order No.

481491



ORE 5-150 EC

Order No. 447706



Order No.

484857

DD 2G 10.8-EC

2-speed cordless drill driver 10.8 V

Technical features

- The powerful all-rounder
- With quick-change system, this enables simple, toolless changing of the angle attachment, drill chuck and bit holder
- The tool is also available as a set in a L-BOXX[®] with a charger and two 4.0 Ah battery packs









Battery pack not included

1\\/	2//"	10	0-EC	C
	J/4	10.	U-EC	

Cordless impact screwdriver 18.0 V

Technical features

Order No.

418005

- Square drive for 3/4" drive sockets
- Powerful impact mechanism: Highest power enables stuck e.g. rusted screw connections to be loosened even in extreme applications
- The tool is also available as a set in a L-BOXX[®] with a quick charger and two 5.0 Ah battery packs

3.		
not	1871111	









IW 1/2" 18.0-EC C

Cordless impact screwdriver 18.0 V

Technical features

Order No.

492612

- Speed command: Three different speed ranges can be set for different applications. One of the benefits is that this prevents small screws from being overtightened
- Integrated LED lamp with afterglow function
- The tool is also available as a set in a L-BOXX[®] with a quick charger and two 5.0 Ah battery packs











Battery pack not included

Order No. 491268

Long protormance **MARAROOD** This is Proformance. This is FLEX.



3-year warranty

Simply register and use the 3-year warranty immediately at warranty.flex-tools.com



Our products are thoroughly tested to ensure FLEX premium quality. That's why with the 3-year guarantee, we offer you a free, all-round carefree package - on all power tools*, Li-ion batteries, the associated chargers and laser measuring devices.

To benefit from the warranty, simply register your device within 30 days of purchase:

- Warranty period extended to three years
- Service certificate in case a repair is required
- Tracking of repair status if the machine is under warranty

*Does not apply to H Class vacuum cleaners.

For more information about our automotive range, please contact your competent specialist dealer



Would you like to have your warranty certificates always on your smartphone

and manage them while on the go?

the service:





FLEX-Elektrowerkzeuge GmbH Bahnhofstrasse 15 71711 Steinheim Germany www.flex-tools.com

The configuration of the machines is the same as the usual basic equipment. Subject to VAT changes, technical changes, price changes and errors. All prices in bold are recommended prices plus VAT.

or