

BBE 16-3 110

Brushing machine

Order no. 535340

GTIN 4030293291805



- + Brush attachment with detachable protective cover and suction connection Ø 32 mm for low-dust work. Including guide stop for processing narrow workpieces
- + For low-dust work in the metal and stainless steel area. Also for brushing, structuring and cleaning wood surfaces
- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Spindle lock



Soft Start



Constant Drive Control



Temperature Monitoring



Overload Protection



Restart Protection



Spindle-lock



Dust extraction

Technical data

Power consumption	1600 W
Power output	950 W
Voltage	230 V
Frequency	50/60 Hz
No-load speed	1400 - 3900 rpm
Brush diameter	120 mm
Brush width	100 mm
Tool fixture, brush sander	19mm
Cable length	4,0 m
Dimensions WxLxH	335 x 215 x 220 mm
Weight	2,9 kg

Standard equipment

- 1 Extraction hood (461547)
- 1 Brush strip (461563)
- 1 Bail handle (535632)

www.flex-tools.com

this is performance **FLEX**