

LWE 15-3 100

1500 watt wet stone polisher with variable speed, plug for isolating transformer, 100 mm

Order no. 535583

GTIN 4030293294233



- + High torque for maximum material removal and optimum surface quality
- + Microprocessor control with soft start, restart protection after power failure, temperature monitoring, overload protection, CDC-electronic feedback control
- + Anti-Kickback - this shuts down the motor on the disc being blocked
- + Electronics: Speed preselection with 6 settings
- + The water feed and control system is located below the housing, which makes operation and precise dosing easy. An unobstructed grip area is provided directly above the backing pad
- + 2 m special hose: No additional hose safety devices required. Increases flexibility, reduces weight and prevents risk of injury from hose clips
- + Quick-fit brass coupling: for 1/2 water hose
- + Contour plug: can be connected only to an isolating transformer. For safety reasons, operation is permitted only connected to the FLEX TT 2000 isolating transformer
- + Grip hood for easy handling and precise working
- + Bail handle: Secure grip, even when working on vertical surfaces
- + Spindle lock

Technical data

Power consumption	1500 W
Voltage	230 V
Frequency	50/60 Hz
No-load speed	1400 - 3900 rpm
Cable length	5 m
No-load speed	

Standard equipment

1 Bail handle
1 Water supply/hose
1 Cable clip

www.flex-tools.com

this is proformance **FLEX**