


LD 16-8 125 R, Kit Turbo-Jet II

Compact renovation grinder for dust-free grinding close to edges, 125 mm

Order no. 504939

GTIN 4030293230682

- + Electronic control: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- + Dust extraction: prevents dust nuisance, reduces disc wear, keeps the concrete pores open for the new coating
- + Reliable 1600 watt high-performance motor with sufficient power reserves
- + Anti-Kickback - this shuts down the motor on the disc being blocked
- + Guard with pivoting segment to allow grinding right up to the wall. Height-adjustable to the disc height and for optimum dust extraction
- + With steplessly adjustable, vibration-proof, ergonomic bail handle, for optimum handling and machine control
- + For fast hose connection. FLEX clip connection for Ø 32 mm snap connection included in the standard equipment
- + Recessed spindle lock, to avoid unintentional activation
- + Ideally suited for processing walls, ceilings and floors. Efficient and economic working thanks to optimum coordination between machine and sanding disc
- + Turbo-Jet grinding disc with optimum removal rate. The large number of diamond segments provides a considerably quieter operating performance and a more attractive sanding pattern. Ideal for surface grinding on mineral substrates.



Technical data

Power consumption	1600 W
Power output	950 W
Voltage	230 V
Frequency	50/60 Hz
Disc diameter	125 mm
No-load speed	7800 rpm
Tool holder, renovation grinder	M14
Cable length	4.0 m
Weight	3.1 kg

Standard equipment

- 1 Turbo-Jet diamond grinding disc (453773)
- 1 Extraction hood with pivoting edge segment (498475)
- 3 Cable clip (252188)
- 1 Hexagon socket wrench (102229)
- 1 Face pin spanner (392537)
- 1 Carrying case L-BOXX® (414093)
- 1 Case insert (414131)
- 1 Bail handle