

LD 18-7 125 R, Kit TH-Jet

1750 watt powerful grinding machine for working close to edges, 125 mm

Order no. 408611

GTIN 4030293173941



- + Microprocessor electronics: with consistent speed control, soft start, overload protection and temperature monitoring
- + Reliable 1800 watt high-performance motor with sufficient power reserves
- + Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- + Recessed spindle lock, to avoid unintentional activation
- + With steplessly adjustable, vibration-proof, ergonomic bail handle, for optimum handling and machine control
- + Guard with pivoting segment to allow grinding right up to the wall. Height-adjustable to the disc height and for optimum dust extraction
- + Adapter for FLEX clip-system as standard equipment
- + 125 mm diameter, ideal for application on small or medium size floor, wall or ceiling areas
- + Diamond grinding disc suitable for grinding concrete parts, roughing old weathered concrete, hard cement plaster, removing shuttering protrusions and concrete runs, hardened epoxy resin coatings and the natural sintering on concrete components. High grinding capacity and service life from the innovative segment design. Optimal ground preparation for further coating.



Soft Start



Temperature Monitoring



Overload Protection



Restart Protection



Spindle-lock



Dust extraction



Carrying case

Technical data

Power consumption	1750 W
Power output	1200 W
Voltage	230 V
Frequency	50/60 Hz
Disc diameter	125 mm
No-load speed	7000 rpm
Tool holder, renovation grinder	M14
Cable length	4.0 m
Dimensions WxLxH	445 x 155 x 86 mm
Weight	4.2 kg

Standard equipment

- 1 Thermo-Jet diamond grinding disc (359378)
- 1 Extraction hood with pivoting edge segment (498475)
- 3 Cable clip (252188)
- 1 Face pin spanner (392537)
- 1 Bail handle
- 1 Hexagon socket wrench (102229)
- 1 Clamping nut M 14 (534344)
- 1 Carrying case (535761)