

CHE 5-40 SDS-max

Universal rotary hammer drill, 5 kg, SDS-max

Order no. 439665

GTIN 4030293191839



- + 1150 watt hammer drill and chisel hammer in D-build with high impact energy and low vibrations
- + Function switch with three functions: hammer drilling, chiselling, chisel adjustment
- + Rotation stop for chiselling
- + Ideal for hammer-drilling, diameter 40 mm in masonry and concrete for composite or injection anchoring systems and through-holes
- + For chiselling work when removing plaster and tiles
- + Variable speed, continuous adjustment from 1-6 with "Power Control LED indicator
- + Safety slip clutch: offers protection if the core drill is jammed
- + Decoupled, ergonomic handle with rubberised grip surface. Vibrations are reduced by a sprung damper and additional vibration damping between the housing and handle



Technical data

Power consumption	1150 W
Voltage	230 V
Frequency	50/60 Hz
Tool holder, drill and chisel	SDS-max
Max. single impact energy	10 J
No-load speed	0 - 350 rpm
No-load blows	1300 - 2900 1 rpm
Max. drilling diameter in concrete	40 mm
Max. drilling diameter in masonry (drill bit)	90 mm
Max. drilling diameter in wood	32 mm
Max. drilling diameter in steel	13 mm
Cable length	4,0 m
Dimensions WxLxH	475 x 100 x 260 mm
Weight	6,4 kg

Standard equipment

- 1 Tube of grease (370894)
- 1 Handle
- 1 Carrying case