

# PD 2G 18-EC MD DC

Compact 2-speed cordless percussion drill 18 V

Order no. 534904

GTIN 4030293287440



- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + With switchable anti-kickback function, for constant power transmission without unwanted interruption. Useful for metal work such as thread cutting, step drilling or core drilling
- + Compact, powerful, safe and very flexible in use. The all-rounder for every craftsman
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Robust gearbox housing made of die-cast aluminium
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + Including attachable auxiliary handle, belt clip and bit storage
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



## Technical data

|                                 |                        |
|---------------------------------|------------------------|
| Battery voltage                 | 18 V                   |
| Battery capacity                | 2,5 / 5,0 / 8,0 Ah     |
| Max. torque, hard               | 115 Nm                 |
| Max. torque, soft               | 60 Nm                  |
| No-load speed, 1st gear         | 0 - 600 rpm            |
| No-load speed, 2nd gear         | 0 - 2300 rpm           |
| No-load blows, Setting 1        | 0 - 9600 1 rpm         |
| No-load blows, Setting 2        | 0 - 36800 1 rpm        |
| Chuck clamping width            | 1.5-13 mm              |
| Max. drilling diameter in wood  | 68 mm                  |
| Max. drilling diameter in stone | 13 mm                  |
| Max. drilling diameter in steel | 13 mm                  |
| Dimensions WxLxH                | 180 x 65 x 208 mm      |
| Weight without battery pack     | 1,50 kg                |
| Torque adjustment               | 22+1 Steps             |
| Sound pressure level            | 86 dB(A)               |
| Vibration                       | 11,47 m/s <sup>2</sup> |

## Standard equipment

- 1 Belt clip
- 1 Bit storage
- 1 Handle
- 1 Carrying case L-BOXX® (414085)

