

PD 2G 18-EC HD2

2-speed cordless percussion drill 18,0 V with turbo mode

Order no. 535163

GTIN 4030293290037



- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Maximum torque of 170 Nm for screwing, drilling and percussion drilling, also in extreme applications. The chosen torque setting stays activated when switching from drilling to percussion drilling mode
- + Two mechanical gears combined with turbo mode 2.0 result in four selectable levels - for maximum control and up to 3000 rpm.
- + With switchable anti-kickback function, for constant power transmission without unwanted interruption. Useful for metal work such as thread cutting, step drilling or core drilling
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Robust gearbox housing made of die-cast aluminium
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + Including attachable auxiliary handle, belt clip and bit storage
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

Battery voltage	18 V
Battery capacity	2.5 / 5.0 / 8.0 Ah
Max. torque, hard	170 Nm
No-load speed, 1st gear	0 - 700 rpm
No-load speed, 2nd gear	0 - 3000 rpm
No-load blows, Setting 1	0 - 9600 1 rpm
No-load blows, Setting 2	0 - 40800 1 rpm
Chuck clamping width	1,5-13 mm
Max. drilling diameter in wood	160 mm
Max. drilling diameter in stone	16 mm
Max. drilling diameter in steel	13 mm
Dimensions WxLxH	175.5 x 65 x 214 mm
Weight without battery pack	1.6 kg
Torque adjustment	22+1 Steps
Sound pressure level	87 dB(A)

Standard equipment

- 1 Belt clip
- 1 Bit storage
- 1 Handle
- 1 Carrying case L-BOXX® (414085)

www.flex-tools.com

this is performance **FLEX**