

# L 21-8 180

2100 watt angle grinder, 180 mm

Order no. 392782

GTIN 4030293164314



- + Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- + Ergonomically designed and very slim motor housing provides optimum guidance and handling. An additional vibration damping ring between the motor housing and rear handle reduces the vibrations
- + Soft-start: for a soft start without power overloading
- + SoftVib handgrip for reduced vibration can be mounted in three positions.
- + Rear shaft handle with soft padding for secure grip
- + Switch: with lock-off / lock-on switch
- + Restart protection after power interruption
- + Spindle lock
- + Tool-free adjustment of safety guard
- + Disc guard cover for cutting guard (446.718), as an optional accessory



## Technical data

Power consumption	2100 W
Power output	1250 W
Voltage	230 V
Frequency	50/60 Hz
Max. disc diameter	180 mm
No-load speed	8300 rpm
Tool holder, angle grinder	M14
Cable length	4,0 m
Dimensions WxLxH	495 x 101 x 135 mm
Weight	5,2 kg

## Standard equipment

- 1 Sanding guard (416517)
- 1 SoftVib side handle (325384)
- 1 Clamping nut M 14 (100080)
- 1 Face pin spanner (100110)
- 1 Clamping flange (335282)