

ALC 3/360-G/R 10.8 Set

360° cross-line laser with receiver mode

Order no. 500739

GTIN 4030293227705



- + With one horizontal and two vertical 360° laser lines, individually switchable
- + The lines are at 90° to each other and allow for quick alignment and assembly
- + Plumb function, the vertical cross points are automatically the plumb point
- + Specially coated glasses ensure clean and high-precision laser lines.
- + The green line is easily visible, even in bad lighting conditions
- + Extended range of 100 m, with receiver up to 120 m working range
- + Self-levelling
- + Optical warning signal when self-levelling range exceeded
- + On/Off switch for self levelling function, so that the laser beam can be adjusted manually
- + Brightness control across 3 levels, selection according to ambient brightness or battery status. Level 1 is also the receiver mode
- + Dust- and splash-proof
- + 1/4" and 5/8" thread for tripod
- + With vertical and horizontal levelling the ALC is best suitable for interior finishing, for setting out doors, windows, walls, cupboards, and mirror tiles etc. And for many different setting out jobs on the building site
- + FLEX battery system: suitable for all FLEX 10,8 V battery packs



Technical data

| | |
|------------------------------------|-------------------|
| Number of lines, horizontal | 1 Cont. |
| Number of lines, vertical | 2 Cont. |
| Visible range, horizontal lines | 360° |
| Visible range, vertical lines | 360° |
| Laser class | 2 |
| Max. operating range | 100 m |
| Max. operating range with receiver | 120 m |
| Precision | ± 0,3 mm |
| Self-levelling range | 4° |
| Operating time | 12 h |
| Temperature range | -10 - +40 °C |
| Protection class | IP54 |
| Power supply | Battery system |
| Battery voltage | 10.8 V |
| Battery capacity | 2.5 / 4.0 Ah |
| Dimensions WxLxH | 152 x 88 x 130 mm |
| Weight without battery pack | 0.8 kg |

Standard equipment

- 1 Laser target plate and goggles, green (500763)
- 1 Laser universal bracket (500747)
- 1 Li-Ion rechargeable battery pack 10,8 V (418048)
- 1 Rapid charger 10.8 Volt (418021)
- 1 Carrying case L-BOXX® (414085)