

# GE 6 R-EC

Giraffe® wall and ceiling sander

Order no. 530900

GTIN 4030293247406



- + Light weight: Carbon is a very light material, making the wall and ceiling sander's overall weight much lighter. This reduces the stress on the user and minimises fatigue during sanding over longer periods
- + This unusually light machine offers unique user comfort. The wall and ceiling sander is optimally balanced, which enables perfect guidance as the weight is evenly distributed across the sander. Extremely pleasant to handle thanks to the ergonomically-shaped carbon guide tube and the soft grip insert on the main handle and the spade handle
- + A very flat, gimbal-mounted sanding head with a swivel range of 160° enables high flexibility and optimum adjustment when sanding on walls and ceilings. Another plus point in the shape of the highly-developed planetary gears in the sanding head delivers vibration-free running for perfect surface sanding
- + The sanding head with the innovative backing pad adapts very well to the surface being sanded, and delivers a noticeably improved sanding feel. The great flexibility of the Giraffe® means that no unnecessary pressure needs to be applied in order to achieve optimum results
- + Segment sanding head with rotatable edge segment. This allows the sanding of surface transitions from wall to wall and wall to ceiling. The head's rotation follows the movement of the machine, without interruption of work.
- + Brushless motor with greater efficiency and a longer service life
- + Variable speed, levels from 1-6 with Power Control LED indicator
- + The innovative, textile transport system allows the machine and accessories to be transported effortlessly. The Giraffe® does not have to be mounted and is immediately ready for use
- + According to the assortment of sanding paper ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting
- + Very flexible thanks to an optional 500 mm extension (accessory) for high rooms, can be attached without any tools
- + Effective dust extraction from between the brush ring and the sanding pad prevents clogging of the abrasive and promotes a dust-free working environment
- + Connection option for the FLEX safety vacuum cleaners with flow rate optimisation on the guide tube with the FLEX clip system, anti-static in conjunction with an antistatic suction hose.
- + Dust-proof on/off switch



## Technical data

Power consumption	500 W
Voltage	230 V
Frequency	50/60 Hz
Backing pad diameter	225 mm
No-load speed	1100 - 1680 rpm
Head angle of inclination	160°
Tool holder, wall and ceiling sander	hook and loop
Cable length	5,0 m
Length	1520 mm
Weight	2,84 kg

## Standard equipment

1 Carrying bag (532234)