

# XFE 7-12 80

Eccentric polisher with random orbital

Order no. 447129

GTIN 4030293196919



- + 12 mm orbit for high efficiency
- + Free-spinning drive for hologram-free finishing
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints
- + Especially suitable into the spot-repair area and for difficult shapes. Ideal auxiliary for larger polishers
- + Powerful 700 watt motor with highly-efficient ventilator for optimum cooling
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + VR microprocessor control: with tachogenerator constant speed control, soft start, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Counterweight for smoother operation
- + Cushioned special hook and loop pad for polishing.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + With rubberised resting bar for safe setting down



## Technical data

|                          |                   |
|--------------------------|-------------------|
| Power consumption        | 700 W             |
| Power output             | 425 W             |
| Voltage                  | 230 V             |
| Frequency                | 50/60 Hz          |
| Max. polishing disc size | 80 mm             |
| Max. support plate size  | 75 mm             |
| Polishing stroke         | 12 mm             |
| No-load speed            | 1800 - 5500 rpm   |
| Orbit rate, no load      | 3600 - 10800 rpm  |
| Cable length             | 4.0 m             |
| Dimensions WxLxH         | 320 x 58 x 120 mm |
| Weight                   | 2.1 kg            |

## Standard equipment

1 Special hook-and-loop pad, cushioned (493406)