

DCG L 26-6 230 G-Set

Diamond cutting system, 230 mm

Order no. 494674

GTIN 4030293224155



- + Ready to go straight away, angle grinder with already installed extraction hood in the case. Diamantjet - Standard 230 mm diamond cutting wheel for concrete included
- + Powerful angle grinder L 26-6 230 with soft start, restart protection after power failure, overload protection, CDC-electronic feedback control, anti-kickback function
- + Fully encapsulated extraction hood for efficient dust extraction
- + Direct connection via Flex Clip system
- + Extremely sturdy construction. The stabiliser element prevents distortion caused by the side weight of the angle grinder.
- + Base plate with rollers for easy feed. Can be used with or without a guide rail
- + Depth stop with scale for cutting depth adjustments and individual cuts (plunge cuts) with or without guide rail (max. 55 mm with, 60 mm without guide rail)
- + Side handle can be fitted on either the left or right
- + Case including lid compartment for small parts, storage space for diamond cutting wheel, side handle and 800 mm guide rail.



Technical data

Power consumption	2600 W
Power output	1800 W
Voltage	230 V
Frequency	50/60 Hz
Max. disc diameter	230 mm
No-load speed	6500 rpm
Tool holder, angle grinder	M14
Cable length	4.0 m
Dimensions WxLxH	610 x 195 x 290 mm
Weight	9.18 kg
Cutting depth	60 mm

Standard equipment

- 1 Extraction hood cutting for large angle grinder, 230 mm (471895)
- 1 Diamantjet - diamond cutting disc, universal (500720)
- 1 Guide rail GRS (353280)
- 3 Rubber strip (494593)
- 1 Distance ring (494615)
- 1 SoftVib side handle (325384)
- 1 Clamping nut M 14 (100080)
- 1 Hexagon socket wrench, SW 6 (104167)
- 1 Face pin spanner (100110)
- 1 Carrying case (499579)
- 1 Clamping flange (335282)