

FBE 8-4 140

Belt file TRINOXFLEX

Order no. 453455

GTIN 4030293201071



- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + VE electronic control: for infinitely adjustable belt speed
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Sanding head: rotates through 140°. For use with sanding arms in 9 mm or 30 mm
- + Sanding arm adjustable for 520 mm and 533 mm belt lengths
- + Processing length sanding arm up to approx. 12 cm
- + Sanding belt replacement: quick and tool-free



Technical data

Power consumption	800 W
Power output	425 W
Voltage	230 V
Frequency	50/60 Hz
No-load speed	1400 - 4000 rpm
Belt speed	3 - 8 m/sec
Belt length	533 mm
Belt width	4-30 mm
Cable length	4,0 m
Dimensions WxLxH	320 x 210 x 195 mm
Weight	2,6 kg

Standard equipment

- 1 Sanding attachment, belt file (459593)
- 2 Sanding belt ZIRCOFLEX (303615)
- 2 Sanding belt ZIRCOFLEX (303623)
- 2 Sanding belt ZIRCOFLEX (257105)
- 2 Sanding belt ZIRCOFLEX (257102)
- 2 Sanding belt ZIRCOFLEX (255328)
- 2 Sanding belt ZIRCOFLEX (255329)
- 1 Sanding belt MESHFLEX (318663)
- 1 Sanding belt MESHFLEX (318647)
- 1 Side handle, red (194034)
- 1 Hexagon socket wrench, SW 5 (115460)
- 1 Carrying case L-BOXX® (414085)
- 1 Case insert (457337)