

# PD 2G 18-EC HD2

2-speed cordless percussion drill 18,0 V with turbo mode

Order no. 535163

GTIN 4030293290037



- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Maximum torque of 170 Nm for screwing, drilling and percussion drilling, also in extreme applications. The chosen torque setting stays activated when switching from drilling to percussion drilling mode
- + Two mechanical gears combined with turbo mode 2.0 result in four selectable levels - for maximum control and up to 3000 rpm.
- + With switchable anti-kickback function, for constant power transmission without unwanted interruption. Useful for metal work such as thread cutting, step drilling or core drilling
- + Accelerator trigger with lock-off switch
- + Electronic quick-acting brake
- + Robust gearbox housing made of die-cast aluminium
- + Right/left rotation with safety catch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + Including attachable auxiliary handle, belt clip and bit storage
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



## Technical data

|                                 |                     |
|---------------------------------|---------------------|
| Battery voltage                 | 18 V                |
| Battery capacity                | 2.5 / 5.0 / 8.0 Ah  |
| Max. torque, hard               | 170 Nm              |
| No-load speed, 1st gear         | 0 - 700 rpm         |
| No-load speed, 2nd gear         | 0 - 3000 rpm        |
| No-load blows, Setting 1        | 0 - 9600 1 rpm      |
| No-load blows, Setting 2        | 0 - 40800 1 rpm     |
| Chuck clamping width            | 1,5-13 mm           |
| Max. drilling diameter in wood  | 160 mm              |
| Max. drilling diameter in stone | 16 mm               |
| Max. drilling diameter in steel | 13 mm               |
| Dimensions WxLxH                | 175.5 x 65 x 214 mm |
| Weight without battery pack     | 1.6 kg              |
| Torque adjustment               | 22+1 Steps          |
| Sound pressure level            | 87 dB(A)            |

## Standard equipment

- 1 Belt clip
- 1 Bit storage
- 1 Handle
- 1 Carrying case L-BOXX® (414085)

[www.flex-tools.com](http://www.flex-tools.com)

this is proformance **FLEX**