

L 21-6 230

2100 watt angle grinder, 230 mm

Order no. 391514

GTIN 4030293164307



- + Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- + Ergonomically designed and very slim motor housing provides optimum guidance and handling. An additional vibration damping ring between the motor housing and rear handle reduces the vibrations
- + Soft-start: for a soft start without power overloading
- + Rear shaft handle with soft padding for secure grip
- + Switch: with lock-off / lock-on switch
- + Restart protection after power interruption
- + Spindle lock
- + Tool-free adjustment of safety guard
- + Cutting guard (389.625) or cover for cutting guard (446.068), as an optional accessory



Technical data

Power consumption	2100 W
Power output	1250 W
Voltage	230 V
Frequency	50/60 Hz
Max. disc diameter	230 mm
No-load speed	
Tool holder, angle grinder	M14
Cable length	4,0 m
Dimensions WxLxH	490 x 104 x 90 mm
Weight	5,4 kg

Standard equipment

- 1 Sanding guard (338729)
- 1 SoftVib side handle (325384)
- 1 Clamping flange (335282)
- 1 Sanding/cutting guard (534105)
- 1 Clamping nut M 14 (534344)
- 1 Face pin spanner (483621)

www.flex-tools.com

this is proformance **FLEX**