www.flex-tools.com

this is proformance FLEX

CS 68 18-EC C

Cordless circular saw with pendulum hood 18 V

Order no. 532636

GTIN 4030293264762



- Ideal for traditional applications in dry construction and refurbishing, e.g. for making saw cuts through plasterboard, concrete fibre boards, wood materials, such as formwork panels and chipboard or OSB boards
- Angle scale from 0 ° to 56 °. With preset angles of 22.5°/ 45°, and 56°. Easy to read, precision adjustment via long clamping lever
- High-quality magnesium die-castings for protective cover and base plates
- Guide rails for straight, splinter-free and powerful cuts. The guide rail slots are located directly in the base plate. Compatible with FLEX and other systems
- Brushless motor with greater efficiency and a longer service life
- 18 V EC motor with overload protection and temperature monitoring
- Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- Motor brake stops the saw blade in 2 seconds
- Integrated LED lamp for optimum illumination of the work area.
- Spindle lock: for quick replacement of blades
- With metal bracket for flexible attachment
- Connector for external dust extraction Ø 27, 36 mm
- Woodshaving collection bag for low-dust operation, simple to empty
- LED battery capacity display
- For optimal power output and maximum runtime in demanding applications, the use of the FLEX 18 V/8.0 XT tabless battery is recommended
- FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



Technical data

Battery voltage	18 V
Battery capacity	2.5 / 5.0 / 8.0 Ah
Max. no-load speed	
Cutting depth	0-68 mm
Cutting depth, mitre cut (45°)	0-50 mm
Saw blade diameter	190 mm
Saw blade hole	20 mm
Pivoting range	0.56°
Angle preset	0 / 22,5 / 45°
Dimensions WxLxH	352 x 200 x 273 mm
Weight without battery pack	4.3 kg

Standard equipment

1 Standard circular saw blade with alternating teeth (532703)
1 Parallel stop
1 Dust bag