

GE 6 X-EC

Wall and ceiling sander Eccentric Giraffe®

Order no. 534652

GTIN 4030293284920



- + The random orbital movement is ideal for controlled guidance on the surface, a fine sanding pattern and working close to the edge. This delivers perfect surface finishing
- + Light weight: Carbon is a very light material, making the wall and ceiling sander's overall weight much lighter. This reduces the stress on the user and minimises fatigue during sanding over longer periods
- + This unusually light machine offers unique user comfort. The wall and ceiling sander is optimally balanced, which enables perfect guidance as the weight is evenly distributed across the sander. Extremely pleasant to handle thanks to the ergonomically-shaped carbon guide tube and the soft grip insert on the main handle and the spade handle
- + With wear-free disk brake for controlled contact with the surface to prevent damage
- + A very flat, gimbal-mounted sanding head with a swivel range of 160° enables high flexibility and optimum adjustment when sanding on walls and ceilings
- + The sanding head with the innovative backing pad adapts very well to the surface being sanded, and delivers a noticeably improved sanding feel. The great flexibility of the Giraffe® means that no unnecessary pressure needs to be applied in order to achieve optimum results
- + Brushless motor with greater efficiency and a longer service life
- + Variable speed, levels from 1-6 with Power Control LED indicator
- + The innovative, textile transport system allows the machine and accessories to be transported effortlessly. The Giraffe® does not have to be mounted and is immediately ready for use
- + According to the assortment of sanding paper ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting
- + Very effective suction extraction thanks to a special hole pattern in the backing pad prevents clogging of the sanding pad to ensure dust-free working
- + Very flexible thanks to an optional 500 mm extension (accessory) for high rooms, can be attached without any tools
- + Connection option for the FLEX safety vacuum cleaners with flow rate optimisation on the guide tube with the FLEX clip system, anti-static in conjunction with an antistatic suction hose.
- + Dust-proof on/off switch



Technical data

Power consumption	500 W
Voltage	230 V
Frequency	50/60 Hz
Backing pad diameter	225 mm
No-load speed	5600 - 8500 rpm
Orbit rate, no load	11200 - 17000 rpm
Stroke	4 mm
Head angle of inclination	160°
Tool holder, wall and ceiling sander	hook and loop
Cable length	4,0 m
Length	1520 mm
Weight	2,9 kg

Standard equipment

- 1 Protection pad (534323)
- 1 Carrying bag (532234)
- 1 Centering aid GE 6 (535461)