

# ALC 3/1-G/R

Self-levelling crossline laser with receiver mode

Order no. 509841

GTIN 4030293232952

- + With one horizontal and two vertical laser lines at a 90° angle plus plumb (red laser line), can be switched individually
- + Plumb function
- + Specially coated glasses ensure clean and high-precision laser lines.
- + Green laser diode
- + The green line is easily visible, even in bad lighting conditions
- + Extends the range from 50 metres up to 70 metres with receiver
- + Self-levelling
- + Optical warning signal when self-levelling range exceeded
- + Self-levelling which can be switched off
- + Simple operation
- + Transportation lock
- + Integrated Li-polymer rechargeable battery
- + 1/4" thread for tripod
- + Ideal for aligning the framework



## Technical data

Number of lines, horizontal	1 Cont.
Number of lines, vertical	2 Cont.
Visible range, horizontal lines	110°
Visible range, vertical lines	110°
Plumb function	Yes
Laser class	2
Max. operating range	20 m
Max. operating range with receiver	70 m
Precision	0,3 / Lot 0,6 mm
Temperature range	-5 - +50 °C
Power supply	Integrated battery
Dimensions WxLxH	60 x 112 x 126 mm
Weight	0,53 kg

## Standard equipment

- 1 Laser wall bracket (428167)
- 1 USB-cable
- 1 USB-charger
- 1 Carrying bag