## this is proformance



## MXE 1000 + WR2 120

1010 watt 1-speed mixer with accelerator trig-

ger switch

Order no. 495883 GTIN 4030293224445

- Large, rugged single-speed gear unit with optimum gear ratio for high torque
- Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- For mixed applications up to 40 kg
- Proven standard mixer is ideal for users operating mainly in the low speed range
- With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...





## Technical data

Power consumption	1010 W
Power output	550 W
Voltage	230 V
Frequency	50/60 Hz
Max. mixing basket diameter	120 mm
Tool holder, mixer	M14
No-load speed, 1st gear	0 - 780 rpm
Clamping collar diameter	53 mm
Cable length	4,0 m
Dimensions WxLxH	405 x 215 x 340 mm
Weight	4,5 kg

## **Standard equipment**

1 Helix paddle WR2 (368881)

1 Open-ended wrench SW 19 (439967)

1 Open-ended wrench SW 22 (439975)