this is proformance



PD 2G 18.0-EC HD C

2-speed cordless percussion drill 18,0 V with

turbo mode

Order no. 515698 GTIN 4030293236219

- Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- Brushless motor with greater efficiency and a longer service life
- Anti-kickback, switches off the motor in case of jamming to prevent the wrist from twisting
- Turbo mode for faster and more powerful drilling, for an up to 27% higher speed of rotation
- Maximum torque of 158 Nm for screwing, drilling and percussion drilling, also in extreme applications. The chosen torque setting stays activated when switching from drilling to percussion drilling mode
- Accelerator trigger with lock-off switch
- Electronic quick-acting brake
- Bobust gearbox housing made of die-cast aluminium
- G Metal quick-clamp chuck with thrust ring and auto lock function
- Right/left rotation with safety catch
- Extendable handle offers user protection even at maximum torque
- Ergonomically designed, non-slip, soft grip handle
- Integrated LED lamp with persistence function
- LED battery capacity display
- Including attachable auxiliary handle, belt clip and bit storage
- FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger







Technical data

| Battery voltage | 18 V |
|---------------------------------|--------------------|
| Battery capacity | 2.5 / 5.0 / 8.0 Ah |
| Max. torque, hard | 158 Nm |
| Max. torque, soft | 70 Nm |
| Torque adjustment | 23 Steps |
| No-load speed, 1st gear | 0 - 700 rpm |
| No-load speed, 2nd gear | 0 - 2500 rpm |
| No-load blows, Setting 2 | 0 - 40000 1 rpm |
| Chuck clamping width | 1,5 - 13 mm |
| Max. drilling diameter in wood | 89 mm |
| Max. drilling diameter in steel | 13 mm |
| Dimensions WxLxH | 182 x 75 x 210 mm |
| Weight without battery pack | 1.7 kg |
| | |

Standard equipment

1 Belt clip 1 Handle

1 Bit storage