

# OSE 2-70x198-EC

Compact orbital sander with speed control

Order no. 530632

GTIN 4030293244726



- + Brushless motor with greater efficiency and a longer service life
- + E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- + Sanding speed suitable for the material thanks to electronic speed adjustment
- + Ideal for sanding filled surfaces on car parts during repair work. For surface sanding the substrate and avoiding unevenness before applying the filler and using a random orbit sander
- + Electronics: Speed preselection with 4 settings, constant speed control by means of tachogenerator, soft start, restart protection
- + Velcro backing pad with bevelled pad geometry and multi-hole system for optimum suction, suitable for all commercially available pads
- + Lightweight, compact one-handed orbital sander, very ergonomic and low-vibration thanks to special balancing for fatigue-free and joint-friendly work
- + Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- + Effective dust extraction thanks to integrated extractor for dust-free working with filter cartridge
- + External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected



## Technical data

Power consumption	260 W
Voltage	230 V
Stroke	2 mm
Backing pad length	198 mm
Backing pad width	70 mm
Orbit rate, no load	10000 - 20000 rpm
No-load speed	5000 - 10000 rpm
Cable length	4,0 m
Dimensions WxLxH	210 x 75 x 124 mm
Weight	1,3 kg

## Standard equipment