

CHE 2-28 SDS-plus

Universal rotary hammer drill, 2,5 kg, SDS-plus

Order no. 413666

GTIN 4030293177130



- + Light 800 watt hammer drill and chisel hammer, pistol-shaped with the clockwise/anticlockwise rotation function
- + Hammer drilling
- + Max. drilling range up to 28 mm in concrete
- + Ideal for drilling and hammer drilling, diameters from 4-18 mm in masonry and concrete for dowel fixings or through-holes.
- + For light-duty chiselling work when removing plaster and tiles
- + Rotation stop for chiselling
- + Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- + Depth limit gauge: for precision drilling
- + Accelerator switch with lock-on function



Technical data

Power consumption	800 W
Voltage	230 V
Frequency	50/60 Hz
Tool holder, drill and chisel	SDS-plus
Max. single impact energy	2.7 J
No-load speed	0 - 1300 rpm
No-load blows	0 - 4000 1 rpm
Max. drilling diameter in concrete	28 mm
Max. drilling diameter in wood	30 mm
Max. drilling diameter in steel	13 mm
Cable length	4.0 m
Dimensions WxLxH	360 x 85 x 200 mm
Weight	2.65 kg

Standard equipment

- 1 Handle (417661)
- 1 Depth stop (417769)
- 1 Carrying case L-BOXX® (414085)
- 1 Case insert (414042)

www.flex-tools.com

this is proformance **FLEX**