www.flex-tools.com

this is proformance FLEX

# PD 2G 18-EC HD2


## 2-speed cordless percussion drill 18,0 V with turbo mode

## Order no. 535163

## GTIN 4030293290037




- Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- Brushless motor with greater efficiency and a longer service life
- Maximum torque of 170 Nm for screwing, drilling and percussion drilling, also in extreme applications. The chosen torque setting stays activated when switching from drilling to percussion drilling mode
- Two mechanical gears combined with turbo mode 2.0 result in four selectable levels – for maximum control and up to 3000 rpm.
- With switchable anti-kickback function, for constant power transmission without unwanted interruption. Useful for metal work such as thread cutting, step drilling or core drilling
- Accelerator trigger with lock-off switch
- Electronic quick-acting brake
- Robust gearbox housing made of die-cast aluminium
- Right/left rotation with safety catch
- Ergonomically designed, non-slip, soft grip handle
- Integrated LED lamp with persistence function
- Including attachable auxiliary handle, belt clip and bit storage
- LED battery capacity display
- FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger




### Technical data

| | |
|---|---|
| Battery voltage | 18 V |
| Battery capacity | 2.5 / 5.0 / 8.0 Ah |
| Max. torque, hard | 170 Nm |
| Max. torque, soft | 75 Nm |
| No-load speed, 1st gear | 0 - 700 rpm |
| No-load speed, 2nd gear | 0 - 3000 rpm |
| No-load blows, Setting 1 | 0 - 9600 1 rpm |
| No-load blows, Setting 2 | 0 - 40800 1 rpm |
| Chuck clamping width | 1,5-13 mm |
| Max. drilling diameter in wood | 160 mm |
| Max. drilling diameter in stone | 16 mm |
| Max. drilling diameter in steel | 13 mm |
| Dimensions WxLxH | 175.5 x 65 x 214 mm |
| Weight without battery pack | 1.6 kg |
| Torque adjustment | 22+1 Steps |
| Sound pressure level | 87 dB(A) |

### Standard equipment

1 Belt clip
1 Bit storage
1 Handle
1 Carrying case L-BOXX® (414085)
1 Case insert (536312)