

SE 16-2 125/150

SUPRAFLEX, the sanding specialist for painted surfaces, wood, stone and metal

Order no. 534832

GTIN 4030293286726



- + Sanding specialist for refurbishing, renovating, modernising, processing stainless steel, metal, natural/artificial stone, wood surfaces, painted surfaces
- + VR microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Powerful 1600 watt motor with highly-efficient ventilator for optimum cooling
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + The combination of planetary and angular gears reduces noise to an absolute minimum
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + Completely cast electronic components prevents damage due to metal dust. Protective guard on the winding end of the armature and plated winding on the armature. The 3-fold winding protection reduces motor wear, increases service life.
- + Guard with pivoting edge segment
- + Genuine operation thanks to conveniently placed and dust-protected on/off switch
- + Spindle lock



Technical data

Power consumption	1600 W
Voltage	230 V
Frequency	50/60 Hz
Max. disc diameter	150 mm
Max. support plate size	150 mm
No-load speed	800 - 2200 rpm
Tool holder, rotary grinder	M14
Cable length	4.0 m
Cable type	Red plug
Dimensions WxLxH	380 x 150 x 120 mm
Weight	2.9 kg

Standard equipment

- 1 Handle (450774)
- 1 Face pin spanner (398365)
- 1 Hook-and-loop backing pad (535707)
- 1 Extraction hood with pivoting edge segment (498475)
- 1 Hose clip

www.flex-tools.com

this is proformance **FLEX**