

# CHE 2-26 18.0-EC

Cordless rotary hammer drill 18,0 V

Order no. 478482

GTIN 4030293213692



- + Brushless motor with greater efficiency and a longer service life
- + Powerful motor with 2.6 joules of impact energy and a high rate of removal
- + Function switch with four functions: drilling, hammer drilling, chiselling, chisel adjustment
- + Rotation stop for chiselling
- + Ideal for daily use for drilling and chiselling in concrete, brickwork, timber and metal
- + Drilling chuck can be removed without tools
- + Quick tool change: universal application, with SDS Plus drill chuck or 13 mm quick-release chuck
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Decoupled, ergonomic handle with rubberised grip surface. Vibrations are reduced by a sprung damper and additional vibration damping between the housing and handle
- + Accelerator switch with lock-on function
- + Robust gearbox housing made of die-cast aluminium
- + Electronic quick-acting brake
- + Non-rotating additional handle with depth stop
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + FLEX battery system: suitable for FLEX 18,0 V/5,0 Ah battery packs. Delivery does not include battery and charger



## Technical data

|                                    |                   |
|------------------------------------|-------------------|
| Battery voltage                    | 18 V              |
| Battery capacity                   | 5,0 / 8,0 Ah      |
| Tool holder, drill and chisel      | SDS-plus          |
| Max. single impact energy          | 2,6 J             |
| No-load speed                      | 0 - 980 rpm       |
| No-load blows                      | 0 - 4350 1 rpm    |
| Max. drilling diameter in concrete | 26 mm             |
| Max. drilling diameter in wood     | 30 mm             |
| Max. drilling diameter in steel    | 13 mm             |
| Dimensions WxLxH                   | 360 x 85 x 230 mm |
| Weight without battery pack        | 3,18 kg           |

## Standard equipment

- 1 Chuck (468835)
- 1 Handle (436364)
- 1 Depth stop (417769)
- 1 Carrying case L-BOXX® (414093)
- 1 Case insert (488356)