

# LE 15-11 125


Variable-speed 1500 watt angle grinder, 125 mm

Order no. 447722

GTIN 4030293197329



- + Microprocessor control with soft start, restart protection after power failure, temperature monitoring, CDC-electronic feedback control
- + Highly efficient and resilient motor for more power output
- + Anti-Kickback - this shuts down the motor on the disc being blocked
- + Effective cooling and optimised carbon geometry ensure a long service life
- + Extensive dust protection for motor and gears
- + Compact and ergonomic shape
- + More ergonomic handling due to inclined side handle
- + Tool-free adjustment of safety guard
- + Lockable slide switch
- + Spindle lock
- + This universal angle grinder is suited for steel/metal surface finishing, for work on the site/renovation as well as for vehicle bodywork and construction firms
- + SoftVib handgrip with integrated, patented locknut wrench and vibration damping
- + Please note the maximum speed (rpm) of the accessories



## Technical data

Power consumption	1500 W
Power output	960 W
Voltage	230 V
Frequency	50/60 Hz
Max. disc diameter	125 mm
No-load speed	2800 - 11500 rpm
Tool holder, angle grinder	M14
Cable length	4.0 m
Dimensions WxLxH	310 x 75 x 105 mm
Weight	2.3 kg

## Standard equipment

- 1 Sanding guard (436860)
- 1 SoftVib side handle (530903)
- 1 Clamping flange (335282)
- 1 Clamping nut M 14 (100080)
- 1 Cutting guard clip (534108)