

# IW 1/2" 1500 18-EC C

Cordless impact wrench 18 V

Order no. 532063

GTIN 4030293259034



- + Brushless motor with greater efficiency and a longer service life
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Compact design with die-cast aluminium machine head. Extremely durable and impact-resistant
- + Speed Command: three different speed settings for a variety of applications. Prevents, among others, over tightening of small screws
- + Auto-Stop mode: When tightening, the machine stops as soon as the blow starts. When loosening, the machine stops as soon as the blow stops. Suitable to prevent over-tightening of the screw or nut.
- + Integrated LED light that can be set to five different levels
- + Accelerator trigger with lock-off switch
- + Tool holder square drive for 1/2" impact sockets.
- + Decoupled, ergonomic handle with rubberised grip surface. Vibrations are reduced by a sprung damper and additional vibration damping between the housing and handle
- + Right/left rotation with safety catch
- + Electronic quick-acting brake
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



## Technical data

|                             |                    |
|-----------------------------|--------------------|
| Battery voltage             | 18 V               |
| Battery capacity            | 2.5 / 5.0 / 8.0 Ah |
| Torque settings             | 3 Steps            |
| Max. torque                 | 1500 Nm            |
| Max. loosening torque       | 2000 Nm            |
| No-load speed, 1st gear     | 0 - 500 rpm        |
| No-load speed, 2nd gear     | 0 - 1000 rpm       |
| No-load speed, 3rd gear     | 0 - 1900 rpm       |
| No-load blows               | 0 - 2350 1 rpm     |
| Tool holder, impact drill   | 1/2" outside       |
| Dimensions WxLxH            | 199 x 98 x 243 mm  |
| Weight without battery pack | 2.9 kg             |

## Standard equipment