this is proformance



JSP 12-EC

Cordless jigsaw 12 V Order no. 531317 GTIN 4030293251571

- New generation of brushless motors delivering high efficiency and performance
- Continuously variable cutting speed setting via potentiometer wheel with automatic start-up in position A
- Tool-free saw blade change with quick-clamping system and eject function
- Orbital stroke: 4 settings for higher cutting rate
- Double roller jigsaw blade guide for precise cuts with accurate angles
- Free view of the marking thanks to integrated blow function
- Perfect ergonomics thanks to ideally located SoftGrip surfaces
- Low-vibration and comfortable sawing
- Saw bench adjustment for bevel cuts of up to 45°, 0-lock. Can be set off backwards for sawing close to edges
- Stable base plate with removable plastic guide block for the protection of delicate surfaces
- CE Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- With automatic start-up, overload protection
- Vacuum flange Ø 27 mm, for a cleaner workplace and clear view of the cut
- Removable chip screen, for tear-free cuts and for guiding the saw blade
- Integrated LED lamp for optimum illumination of the work area.
- LED battery capacity display
- FLEX battery system: suitable for all FLEX 12 V battery packs. Delivery does not include battery and charger





Technical data

| Battery voltage | 12 V |
|--------------------------------|-------------------|
| Battery capacity | 2.5 / 5.0 Ah |
| Orbit rate, no load | 800 - 3000 rpm |
| Stroke | 23 mm |
| Pendulum stroke stages | 4 Steps |
| Speed settings | 1-5 +A Steps |
| Pivoting range | 0-45° |
| Max. material thickness, wood | 90 mm |
| Max. material thickness, metal | 10 mm |
| Dimensions WxLxH | 220 x 69 x 183 mm |
| Weight without battery pack | 1.46 kg |
| Weight | |
| | |

Standard equipment

- 1 Protection against flying swarf, closed
- 1 Anti-splinter guard (490229)
- 1 Extraction adapter Ø 27
- 1 Hexagon socket wrench, SW 3 1 Sliding shoe
- 1 Carrying case L-BOXX® (414085)
- 1 Case insert (533166)