

PE 14-3 125

Ergonomic polisher with speed control trigger

Order no. 406813

GTIN 4030293172791



- + With its wide speed range it is perfect for working with polishing pads from Ø 80 mm upto max Ø 160 mm
- + Powerful 1400 watt motor with highly-efficient ventilator for optimum cooling
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Accelerator switch for a slow and gentle start
- + VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Spindle lock
- + 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions



Throttle switch



Soft Start



Constant Drive Control



Temperature Monitoring



Overload Protection



Restart Protection



Spindle-lock

Technical data

Power consumption	1400 W
Power output	880 W
Voltage	230 V
Frequency	50/60 Hz
Max. polishing disc size	160 mm
Max. support plate size	125 mm
No-load speed	1100 - 3700 rpm
Cable length	4.0 m
Cable type	PUR
Dimensions WxLxH	375 x 84 x 120 mm
Weight	2.2 kg

Standard equipment

1 Handle (450774)