

MXE 18.0-EC/5.0 Set + HP2 120

2-speed cordless mixer with 3-level speed switch 18.0 V

Order no. 495972

GTIN 4030293224520

- ⊕ Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- ⊕ Brushless motor with greater efficiency and a longer service life
- ⊕ Large, rugged 2-gear unit with optimum ratios for powerful torque and correct speed for different materials
- ⊕ Comfortable 3-level switch can be reached from the grip position without interrupting work, protected by a rubber sleeve. Level 1: cleaning, level 2: stirring up, level 3: mixing
- ⊕ Rotary switch to set the optimum mixing speed. Speed 1: for highly viscous materials, speed 2: for medium and low viscosity materials
- ⊕ Accelerator switch for a slow and gentle start
- ⊕ On/off switch with lock and protection
- ⊕ The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- ⊕ Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- ⊕ Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- ⊕ Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- ⊕ Patented spindle lock with start-up protection. For tool-less exchange of the mixing paddle
- ⊕ For mixed applications up to 30 kg
- ⊕ With mixing paddle HP2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...
- ⊕ FLEX battery system: suitable for all FLEX 18 V battery packs



Technical data

Battery voltage	18 V
Battery capacity	2,5 / 5,0 / 8,0 Ah
Max. mixing basket diameter	120 mm
Tool holder, mixer	M14
No-load speed, 1st gear	0 - 210/325/530 rpm
No-load speed, 2nd gear	0 - 320/490/780 rpm
Clamping collar diameter	53 mm
Number of supplied batteries	2 Cont.
With charger	Yes
Dimensions WxLxH	355 x 230 x 320 mm
Weight without battery pack	4,1 kg

Standard equipment

- 1 Helix paddle HP2 (534027)
- 1 Open-ended wrench SW 22 (439975)
- 2 Li-Ion rechargeable battery pack 18 V (532733)
- 1 Rapid charger 12/18 V (532280)

www.flex-tools.com

this is proformance

FLEX