this is proformance

FLEX

ORE 5-150 EC Set

Powerful random-orbit sander with speed con-

trol, 150 mm

Order no. 486817 GTIN 4030293218789

- 150 mm handy random-orbit sander with the best ergonomics and special balancing system for low-vibration operation. Provides comfortable and joint-friendly working conditions
- Brushless motor with greater efficiency and a longer service life
- Haterial-compatible sanding speed by adjustable speed
- Effective dust extraction thanks to integrated extractor for dust-free working with filter cartridge
- Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- External dust extraction Ø 27 mm, adapter SAD-C 27 AS or antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- PES filter cartridge for dust-free and efficient working
- Velcro backing pad available in three degrees of hardness: ultra-soft, soft and hard
- Velcro backing pad with multi-hose system for optimum extraction, suited to all standard 150 diameter abrasives
- Especially suitable for overhead work





Technical data

Power consumption	400 W
Voltage	230 V
Frequency	50/60 Hz
Backing pad diameter	150 mm
Stroke	5 mm
No-load speed	4000 - 10000 rpm
Orbit rate, no load	8000 - 20000 rpm
Diameter dust extraction connection	Ø 27
Cable length	4.0 m
Dimensions WxLxH	230 x 150 x 125 mm
Weight	1.4 kg

Standard equipment

1 Hook-and-loop sanding pad medium (464120)

1 PES microfilter cartridge (486833)

1 Hexagon socket wrench (392731)

1 Carrying case L-BOXX® (414093)

1 Case insert (486868)