

# ID 1/4" 18-EC HD2 C

Cordless impact wrench 18 V with bit ejector

Order no. 535167

GTIN 4030293290075



- + Extremely high speed and torque enable efficient work
- + Its compact and lightweight design makes it ideal for screwdriving in confined spaces
- + Tap mode for self-tapping screws in sheet metal parts with a high-quality finish. This prevents screws from being overtightened and damaging the surface. Two adjustment options for thin and thick sheet metal parts
- + With bit ejector for quick and easy bit change
- + 360° LED ring light on the head for optimum illumination of the work area, dimmable, adjustable to 5 brightness levels
- + Speed Command: three different speed settings for a variety of applications. Prevents, among others, over tightening of small screws
- + Brushless motor with greater efficiency and a longer service life
- + 1/4" hex tool holder
- + Electronic quick-acting brake
- + Right/left rotation with safety catch
- + Robust die-cast aluminium gearbox housing with insulating cap
- + Ergonomically designed, non-slip, soft grip handle
- + Including belt clip and bit storage
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger



## Technical data

|                             |                          |
|-----------------------------|--------------------------|
| Battery voltage             | 18 V                     |
| Battery capacity            | 2,5 / 4,0 / 5,0 / 8,0 Ah |
| Torque settings             | 3 Steps                  |
| Max. torque, setting 1      | 70 Nm                    |
| Max. torque, setting 2      | 100 Nm                   |
| Max. torque, setting 3      | 240 Nm                   |
| No-load speed               | 0 - 4100 rpm             |
| No-load speed, 1st gear     | 0 - 1500 rpm             |
| No-load speed, 2nd gear     | 0 - 2000 rpm             |
| No-load speed, 3rd gear     | 0 - 4100 rpm             |
| No-load blows               | 0 - 4550 1 rpm           |
| No-load blows, setting 1    | 0 - 3000 1 rpm           |
| No-load blows, setting 2    | 0 - 4000 1 rpm           |
| No-load blows, setting 3    | 0 - 4550 1 rpm           |
| Tool holder, impact drill   | 1/4" inside              |
| Dimensions WxLxH            | 114 x 76 x 208 mm        |
| Weight without battery pack | 1,1 kg                   |

## Standard equipment

- 1 Bit storage
- 1 Belt clip

[www.flex-tools.com](http://www.flex-tools.com)

this is proformance **FLEX**